

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 1 of 8

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

3215 Paint sealing 400 ml

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Polishes and wax blends

##### 1.3. Details of the supplier of the safety data sheet

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	Telefax: +49 7941-9205 4090
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Götz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

##### 1.4. Emergency telephone number:

+49 761-19 240

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: F+ - Extremely flammable, N - Dangerous for the environment

R phrases:

Extremely flammable.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

###### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Aerosol: Aerosol 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Toxic to aquatic life with long lasting effects.

##### 2.2. Label elements

Signal word: Danger

Pictograms: GHS02-GHS09



###### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 2 of 8

#### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P273 Avoid release to the environment.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Oils/waxes, containing solvents, aromatics removed

##### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
923-037-2	Hydrocarbons, C10-C12, isoalkanes, < 2% aromatics	40 - < 50 %
64742-48-9	Xn - Harmful, N - Dangerous for the environment R10-51-53-65-66	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411	
01-2119471991-29		
265-150-3	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	0.1 - < 5 %
64742-48-9	Xn - Harmful R10-52-53-65-66-67	

Full text of R-, H- and EUH-phrases: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). First aider: Pay attention to self-protection! Move victim out of danger zone. Never give anything by mouth to an unconscious person or a person with cramps. Remove contaminated, saturated clothing immediately.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Put victim at rest, cover with a blanket and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

##### After contact with eyes

Protect uninjured eye. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

##### After ingestion

Seek medical advice immediately. If unconscious place in recovery position and seek medical advice. Do NOT induce vomiting.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 3 of 8

#### **4.2. Most important symptoms and effects, both acute and delayed**

No data available

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Atomized water. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. alcohol resistant foam.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Im Brandfall können entstehen: Gefährliche Zersetzungsprodukte.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Wear personal protection equipment.

#### **Additional information**

In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8. Use personal protection equipment. Remove all sources of ignition. Avoid contact with skin and eyes. Provide adequate ventilation as well as local exhaustion at critical locations. Avoid breathing dust/fume/gas/mist/vapours/spray. Vapours are heavier than air and will spread at floor level.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

#### **6.4. Reference to other sections**

Safe handling: see section 7. Personal protection equipment: see section 8.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Personal protection equipment: see section 8 Use only in well-ventilated areas. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes. Do not spray on naked flames or any incandescent material. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

##### **Advice on protection against fire and explosion**

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting. Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

##### **Further information on handling**

storage temperature: 15 - 30°C

#### **7.2. Conditions for safe storage, including any incompatibilities**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 4 of 8

#### Requirements for storage rooms and vessels

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on storage compatibility

Keep away from: Oxidizing agents. Strong acid. Strong alkali

Keep away from food, drink and animal feedingstuffs.

Do not store together with: Self-reactive substances and mixtures

#### Further information on storage conditions

No hazardous reaction when handled and stored according to provisions.

#### 7.3. Specific end use(s)

Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### Additional advice on limit values

SECTION 16: Other information

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Protective and hygiene measures

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

NBR (Nitrile rubber).

Thickness of the glove material &gt;0,4 mm / &gt; 480 min

Neoprene

Thickness of the glove material &gt;0,4 mm

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 5 of 8

#### Test method

pH-Value:	not determined
<b>Changes in the physical state</b>	
Melting point:	not determined
Initial boiling point and boiling range:	-44 °C
Flash point:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Ignition temperature:	200 °C
Decomposition temperature:	not determined
Density (at 24 °C):	0,645 g/cm <sup>3</sup>
Water solubility:	insoluble
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

The product is stable under storage at normal ambient temperatures.  
Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from heat.

### 10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents. strong alkalis

### 10.6. Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>). Carbon monoxide. Nitrogen oxides (NO<sub>x</sub>).

### Further information

No data available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicokinetics, metabolism and distribution

No data available

#### Acute toxicity

No data available

#### Irritation and corrosivity

Has degreasing effect on the skin.

#### Sensitising effects

No data available

#### STOT-single exposure

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 6 of 8

**Severe effects after repeated or prolonged exposure**

No data available

**Carcinogenic/mutagenic/toxic effects for reproduction**

No data available

**Aspiration hazard**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience****Observations relevant to classification**

No data available

**Other observations**

No data available

**Further information**

No data available

## SECTION 12: Ecological information

**12.1. Toxicity**

No data available

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Advice on disposal**

Remove according to the regulations.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 7 of 8

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances  
Classified as hazardous waste.

#### SECTION 14: Transport information

##### Land transport (ADR/RID)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Transport category: 2  
Tunnel restriction code: D

##### Other applicable information (land transport)

E1

##### Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L

##### Other applicable information (inland waterways transport)

E1

##### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2, see SP63  
Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
EmS: F-D, S-U

##### Other applicable information (marine transport)

E1

##### Air transport (ICAO)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
Hazard label: 2.1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Print date: 12.08.2015

Product code: 91253

Page 8 of 8

Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Other applicable information (air transport)**

Passenger-LQ: Y203  
E0  
00000000005: Y203  
E1

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 50 % (322,5 g/l)

**National regulatory information**

Employment restrictions: Observe employment restrictions for young people.  
Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Relevant R-phrases (Number and full text)**

10	Flammable.
51	Toxic to aquatic organisms.
52	Harmful to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

**Relevant H- and EUH-phrases (Number and full text)**

H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*