

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

2295 Rust converter professional 400 ml

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Anti-corrosive paints, containing solvents, high in aromatics

##### 1.3. Details of the supplier of the safety data sheet

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	Telefax: +49 7941-9205 4090
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Götz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

##### 1.4. Emergency telephone number:

+49 761-19 240

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Harmful if swallowed.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause respiratory irritation.

May cause drowsiness or dizziness.

##### 2.2. Label elements

###### Regulation (EC) No. 1272/2008

###### Hazard components for labelling

acetone; propan-2-one; propanone

butan-1-ol; n-butanol

epoxy resin (number average molecular weight  $\leq$  700), reaction product: bisphenol-A-(epichlorhydrin)

1,2,3-trihydroxybenzene, pyrogallol

**Signal word:** Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 2 of 10

#### Pictograms:



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Anti-corrosive paints, containing solvents, high in aromatics

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 3 of 10

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
115-10-6	dimethyl ether			60 - < 70 %
	204-065-8	603-019-00-8		
	Flam. Gas 1; H220			
67-64-1	acetone; propan-2-one; propanone			10 - < 20 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
123-86-4	n-butyl acetate			5 - < 10 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
71-36-3	butan-1-ol; n-butanol			5 - < 10 %
	200-751-6	603-004-00-6		
	Flam. Liq. 3, Acute Tox. 4, STOT SE 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3; H226 H302 H335 H315 H318 H336			
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			0.1 - < 5 %
	500-033-5	603-074-00-8		
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H319 H315 H317 H411			

Full text of H and EUH statements: see section 16.

#### Further Information

Full text of R-, H- and EUH-phrases: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

##### After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If unconscious place in recovery position and seek medical advice.

##### After contact with skin

Wash with plenty of water. Change contaminated clothing. In case of skin irritation, consult a physician.

##### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

##### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 4 of 10

The following symptoms may occur: Headache. Drowsiness. Dizziness.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.

##### **Unsuitable extinguishing media**

none

#### **5.2. Special hazards arising from the substance or mixture**

Vapours may form explosive mixtures with air. Combustible.

#### **5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Keep away from sources of ignition - No smoking.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### **6.4. Reference to other sections**

See protective measures under point 7 and 8.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid: Skin contact, Eye contact.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Provide adequate ventilation as well as local exhaustion at critical locations. Keep container tightly closed in a cool place.

##### **Advice on storage compatibility**

Do not store together with: Acid. alkali. Oxidizing agents.

##### **Further information on storage conditions**

Heating causes rise in pressure with risk of bursting.

### **SECTION 8: Exposure controls/personal protection**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 5 of 10

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	-	-		TWA (8 h)	WEL
		50	154		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

##### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

#### 8.2. Exposure controls

##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

##### Eye/face protection

Suitable eye protection: goggles

##### Hand protection

Tested protective gloves must be worn.  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of the glove material > 0,4mm  
 penetration time (maximum wearing period): > 30 min.  
 DIN EN 374

##### Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Avoid contact with skin, eyes and clothes.

##### Respiratory protection

Use suitable breathing apparatus. Filter type: AX (for group 1 low boilers). In case of a maximum contaminant concentration in inhaled air of 100 mL/m<sup>3</sup> (0.01 % by vol.), group 1 may be used for a maximum of 40 min. In case of a maximum contaminant concentration in inhaled air of 500 mL/m<sup>3</sup> (0.05 % by vol.), group 1 may be used for a maximum of 20 min.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 6 of 10

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol  
Colour: clear  
Odour: characteristic

#### Test method

pH-Value: not applicable

#### Changes in the physical state

Melting point: not applicable

Initial boiling point and boiling range: -24,8 °C

Flash point: -42,2 °C

Lower explosion limits: 1,2 vol. %

Upper explosion limits: 32 vol. %

Ignition temperature: 240 °C

**Auto-ignition temperature** > 300

Vapour pressure: 5102 hPa  
(at 20 °C)

Density: 0,73 g/cm<sup>3</sup>

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water

### 9.2. Other information

none

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Special hazards arising from the substance or mixture. There are no data available on the mixture itself.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No data available

### 10.4. Conditions to avoid

Pressurised container: May burst if heated. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

### 10.5. Incompatible materials

Reacts with : Acid. alkali. Oxidizing agents.

### 10.6. Hazardous decomposition products

none

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 7 of 10

**ATEmix calculated**

ATE (oral) 1819,5 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 mg/kg	5800	Rat	RTECS
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50	76 mg/l	Rat	
1330-20-7	xylene				
	dermal	ATE mg/kg	1100		
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		
71-36-3	butan-1-ol; n-butanol				
	oral	ATE mg/kg	500		

**Irritation and corrosivity**

No data available

**Sensitising effects**

No data available

**Carcinogenic/mutagenic/toxic effects for reproduction**

No data available

**STOT-single exposure**

Toxicological data are not available.

**STOT-repeated exposure**

No data available

**Aspiration hazard**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**
**Observations relevant to classification**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 12: Ecological information

**12.1. Toxicity**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 8 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
67-64-1	acetone; propan-2-one; propanone	-0,24

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

No data available

#### 12.6. Other adverse effects

No data available

#### Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### **Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

##### **Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

##### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number:

UN 1950

##### 14.2. UN proper shipping name:

AEROSOLS



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**2295 Rust converter professional 400 ml**

Revision date: 04.04.2017

Product code: 70460

Page 9 of 10

<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es):</b>	2.1
<b>14.4. Packing group:</b>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	yes
----------------------------	-----

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2295 Rust converter professional 400 ml

Revision date: 04.04.2017

Product code: 70460

Page 10 of 10

#### EU regulatory information

2010/75/EU (VOC): 97%; 705 g/l

2004/42/EC (VOC): 97%; 705 g/l

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D): 2 - water contaminating

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*