

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3050 Nano rain repellent longlife**

Revision date: 14.07.2017

Product code: 90178

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

3050 Nano rain repellent longlife

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	Telefax: +49 7941-9205 4090
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Götz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

**1.4. Emergency telephone number:** +49 761-19 240**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

propan-2-ol; isopropyl alcohol; isopropanol

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 14.07.2017

Product code: 90178

Page 2 of 8

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Acid-hardened sealants, high in solvents

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	50 - 100 %
	200-661-7	
	603-117-00-0	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

In case of fire, use sand, extinguishing powder or alcohol resistant foam. Carbon dioxide.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Do not allow water used to extinguish fire to enter

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 14.07.2017

Product code: 90178

Page 3 of 8

drains or waterways. Use water spray jet to protect personnel and to cool endangered containers.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

##### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

##### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

##### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

###### **Advice on safe handling**

Keep container tightly closed. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Wear anti-static footwear and clothing. Keep away from heat. Avoid contact with skin, eyes and clothes. Do not breathe vapour/aerosol. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8).

###### **Advice on protection against fire and explosion**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

##### 7.2. Conditions for safe storage, including any incompatibilities

###### **Requirements for storage rooms and vessels**

Keep container tightly closed and in a well-ventilated place. Never use pressure to empty container. Keep away from sources of ignition - No smoking. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

###### **Advice on storage compatibility**

Keep away from: acid. alkali. Oxidizing agents.

###### **Further information on storage conditions**

Keep away from heat. Keep container tightly closed. Keep away from sources of ignition - No smoking.

##### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

#### SECTION 8: Exposure controls/personal protection

##### 8.1. Control parameters

###### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

##### 8.2. Exposure controls

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 14.07.2017

Product code: 90178

Page 4 of 8

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Protective and hygiene measures

After contact with skin, wash immediately with plenty of water and soap.

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

rubber gloves.

Thickness of the glove material > 0,4 mm

penetration time (maximum wearing period): > 480 min

Breakthrough times and swelling properties of the material must be taken into consideration.

#### Skin protection

Wear antistatic work clothing.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

#### Environmental exposure controls

Do not allow to enter into surface water or drains. No special environmental measures are necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear
Odour:	Alcohol

	Test method
pH-Value:	2,5
<b>Changes in the physical state</b>	
Initial boiling point and boiling range:	82 °C
Flash point:	12 °C
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	425 °C
Vapour pressure: (at 20 °C)	46,51 hPa
Density (at 20 °C):	0,79 g/cm <sup>3</sup>
Viscosity / dynamic: (at 20 °C)	2,78 mPa·s
Solvent content:	> 75

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 14.07.2017

Product code: 90178

Page 5 of 8

Keep away from: acid. alkali. Oxidizing agents.

#### **10.4. Conditions to avoid**

Thermal decomposition can lead to the escape of irritating gases and vapours.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

#### **10.5. Incompatible materials**

No data available

#### **10.6. Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapours.

Carbon dioxide. Carbon monoxide Nitrogen oxides (NOx).

## SECTION 11: Toxicological information

### **11.1. Information on toxicological effects**

#### **Toxicokinetics, metabolism and distribution**

There are no data available on the preparation/mixture itself.

#### **Acute toxicity**

No data available

#### **Sensitising effects**

No data available

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

No data available

#### **STOT-single exposure**

No data available

#### **STOT-repeated exposure**

No data available

#### **Aspiration hazard**

Inhalation causes narcotic effects/intoxication.

#### **Specific effects in experiment on an animal**

No data available

#### **Additional information on tests**

No data available

#### **Practical experience**

#### **Other observations**

Has degreasing effect on the skin.

#### **Further information**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 12: Ecological information

### **12.1. Toxicity**

No data available

### **12.2. Persistence and degradability**

Some of the components are poorly biodegradable.

### **12.3. Bioaccumulative potential**

No data available

### **12.4. Mobility in soil**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 14.07.2017

Product code: 90178

Page 6 of 8

#### 12.5. Results of PBT and vPvB assessment

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

The evaluation was carried out according to the calculation method of the preparation directive.

According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Advice on disposal**

Do not allow to enter into surface water or drains.

##### **Waste disposal number of waste from residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances  
Classified as hazardous waste.

##### **Waste disposal number of used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances  
Classified as hazardous waste.

##### **Contaminated packaging**

Non-contaminated packages may be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1219
<b>14.2. UN proper shipping name:</b>	ISOPROPANOL (ISOPROPYL ALCOHOL)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

#### **Other applicable information (land transport)**

E2

#### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1219
<b>14.2. UN proper shipping name:</b>	ISOPROPANOL (ISOPROPYL ALCOHOL)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	601

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 14.07.2017

Product code: 90178

Page 7 of 8

Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

E2

**Marine transport (IMDG)**

**14.1. UN number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Special Provisions: -  
Limited quantity: 1 L  
EmS: F-E, S-D

**Other applicable information (marine transport)**

E2

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Special Provisions: A180  
Limited quantity Passenger: 1 L  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**Other applicable information (air transport)**

E2

Passenger-LQ: Y341

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 99,7%; 787,6 g/l (auch CH)  
2004/42/EC (VOC): 99,7%; 787,6 g/l (auch CH)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D): 1 - slightly water contaminating

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3050 Nano rain repellent longlife**

Revision date: 14.07.2017

Product code: 90178

Page 8 of 8

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*