

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3215 Paint sealing 400 ml**

Revision date: 31.08.2017

Product code: 91253

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

3215 Paint sealing 400 ml

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Polishes and wax blends

**1.3. Details of the supplier of the safety data sheet**

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	Telefax: +49 7941-9205 4090
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Götz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

**1.4. Emergency telephone number:**

+49 761-19 240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 2 of 9

P391 Collect spillage.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Oils/waxes, containing solvents, aromatics removed

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-48-9	Hydrocarbons, C10-C12, isoalkanes, < 2% aromatics			40 - 50 %
	923-037-2		01-2119471991-29	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411			
106-97-8	butane			30 - < 40 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
74-98-6	propane			10 - < 20 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			0.1 - < 5 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			
75-28-5	isobutane			0.1 - < 5 %
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

#### Labelling for contents according to Regulation (EC) No 648/2004

&gt;= 30 % aliphatic hydrocarbons.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). First aider: Pay attention to self-protection! Move victim out of danger zone. Never give anything by mouth to an unconscious person or a person with cramps. Remove contaminated, saturated clothing immediately.

##### After inhalation

Remove casualty to fresh air and keep warm and at rest. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Put victim at rest, cover with a blanket and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 3 of 9

#### **After contact with eyes**

Protect uninjured eye. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### **After ingestion**

Seek medical advice immediately. If unconscious place in recovery position and seek medical advice. Do NOT induce vomiting.

#### **4.2. Most important symptoms and effects, both acute and delayed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Atomized water. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. alcohol resistant foam.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>)

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Wear personal protection equipment.

#### **Additional information**

In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8. Use personal protection equipment. Remove all sources of ignition. Avoid contact with skin and eyes. Provide adequate ventilation as well as local exhaust at critical locations. Avoid breathing dust/fume/gas/mist/vapours/spray. Vapours are heavier than air and will spread at floor level.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

#### **6.4. Reference to other sections**

Safe handling: see section 7. Personal protection equipment: see section 8.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Personal protection equipment: see section 8 Use only in well-ventilated areas. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes. Do not spray on naked flames or any incandescent material. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 4 of 9

#### Advice on protection against fire and explosion

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

#### Further information on handling

storage temperature: 15 - 30°C

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### Advice on storage compatibility

Keep away from: Oxidizing agents. Strong acid. Strong alkali

Keep away from food, drink and animal feedingstuffs.

Do not store together with: Self-reactive substances and mixtures

##### Further information on storage conditions

No hazardous reaction when handled and stored according to provisions.

#### 7.3. Specific end use(s)

Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

##### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	Consumer DNEL, long-term	oral	systemic	300 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	300 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	300 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	1500 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	systemic	900 mg/m <sup>3</sup>

#### Additional advice on limit values

SECTION 16: Other information

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Protective and hygiene measures

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

##### Eye/face protection

Wear eye/face protection.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 5 of 9

#### Hand protection

NBR (Nitrile rubber).  
 Thickness of the glove material >0,4 mm / > 480 min  
 Neoprene  
 Thickness of the glove material >0,4 mm  
 Recommended glove articles DIN EN 374

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

#### Test method

pH-Value:	not determined
-----------	----------------

#### Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	-44 °C
Flash point:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Ignition temperature:	200 °C
Decomposition temperature:	not determined
Density (at 24 °C):	0,645 g/cm <sup>3</sup>
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Materials to avoid: Strong acid; Strong alkali; Oxidising agent, strong  
 Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from heat.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 6 of 9

#### 10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents. strong alkalis

#### 10.6. Hazardous decomposition products

 Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>).

#### Further information

No data available

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Toxicokinetics, metabolism and distribution

No data available

##### Acute toxicity

No data available

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 mg/kg	>5000	Rat	OECD 401 eq.

##### Irritation and corrosivity

Has degreasing effect on the skin.

##### Sensitising effects

No data available

##### Carcinogenic/mutagenic/toxic effects for reproduction

No data available

##### STOT-single exposure

No data available

##### STOT-repeated exposure

No data available

##### Aspiration hazard

No data available

##### Specific effects in experiment on an animal

No data available

##### Additional information on tests

No data available

#### Practical experience

##### Observations relevant to classification

May be harmful if swallowed, in contact with skin or if inhaled. Has degreasing effect on the skin. May cause drowsiness or dizziness.

##### Other observations

No data available

#### Further information

May be harmful if swallowed, in contact with skin or if inhaled.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 7 of 9

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
75-28-5	isobutane	2,8

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Remove according to the regulations.

##### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

##### Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

##### Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances  
Classified as hazardous waste.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Transport category:	2
Tunnel restriction code:	D

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3215 Paint sealing 400 ml**

Revision date: 31.08.2017

Product code: 91253

Page 8 of 9

**Other applicable information (land transport)**

E1

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L

**Other applicable information (inland waterways transport)**

E1

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2, see SP63
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	See SP277
EmS:	F-D, S-U

**Other applicable information (marine transport)**

E1

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es):</b>	2.1
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Other applicable information (air transport)**

Passenger-LQ: Y203

E0

00000000005: Y203

E1

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	Hydrocarbons

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3215 Paint sealing 400 ml

Revision date: 31.08.2017

Product code: 91253

Page 9 of 9

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C10-C12, isoalkanes, &lt; 2% aromatics; butane; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics; isobutane

2010/75/EU (VOC): 99,1%; 639,2 g/l

2004/42/EC (VOC): 99,1%; 639,2 g/l

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D): 2 - water contaminating

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*