Telefax: +49 7941-9205 4090

Telephone: +49 170-8548 710



Safety Data Sheet

according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4715 Power rust dissolver, mineral oil free 250 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: KERONA GmbH Street: Zeilbaumweg 15 Place: D-74613 Öhringen Telephone: +49 7941-9205 4080

e-mail: mail@kerona.de Contact person: Dr. Hans Götz

hans.goetz@kerona.de e-mail:

Internet: www.kerona.de 1.4. Emergency telephone +49 761-19 240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH208 Contains Cinnamaldehyde. May produce an allergic reaction.



according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 2 of 9

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]	•			
141-97-9	Ethyl acetoacetate		10 - < 20 %			
	205-516-1					
	Eye Irrit. 2; H319					
123-54-6	acetylacetone, pentane-2,4-dione			0.1 - < 5 %		
	204-634-0	606-029-00-0				
	Flam. Liq. 3, Acute Tox. 4; H226 H3					
107-98-2	1-methoxy-2-propanol; monopropyl		0.1 - < 5 %			
	203-539-1	603-064-00-3				
	Flam. Liq. 3, STOT SE 3; H226 H33					
119-36-8	Methyl salicylate	0.1 - < 5 %				
	204-317-7					
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2	35				
104-55-2	Cinnamaldehyde		0.1 - < 5 %			
	203-213-9					
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2	317				

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

15 % - < 30 % aliphatic hydrocarbons, perfumes (Cinnamal).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). First aider: Pay attention to self-protection! Move victim out of danger zone. Never give anything by mouth to an unconscious person or a person with cramps. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Put victim at rest, cover with a blanket and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Protect uninjured eye. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



KERONA GmbH

according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 3 of 9

After ingestion

Seek medical advice immediately. Do NOT induce vomiting. Rinse mouth thoroughly with water. If unconscious place in recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Atomized water. Carbon dioxide (CO2). Extinguishing powder. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear personal protection equipment.

Additional information

In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Heating causes rise in pressure with risk of bursting.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8. Use personal protection equipment. Remove all sources of ignition. Avoid contact with skin and eyes. Provide adequate ventilation as well as local exhaustion at critical locations. Avoid breathing dust/fume/gas/mist/vapours/spray. Vapours are heavier than air and will spread at floor level.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Personal protection equipment: see section 8 Use only in well-ventilated areas. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes. Do not spray on naked flames or any incandescent material. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Heating causes rise in pressure with risk of bursting. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not





according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 4 of 9

pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

Advice on storage compatibility

Keep away from: Oxidizing agents. Strong acid. Strong alkali

Keep away from food, drink and animal feedingstuffs.

Do not store together with: Self-reactive substances and mixtures

Further information on storage conditions

No hazardous reaction when handled and stored according to provisions.

storage temperature: 5°C - 25°C

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Additional advice on limit values

SECTION 16: Other information

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

Eye/face protection

Wear eye/face protection.

Hand protection

NBR (Nitrile rubber).

Thickness of the glove material >0,4 mm; >480 min

Neoprene

Thickness of the glove material >0,4 mm; >480 min

DIN EN 374

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.





according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: yellow
Odour: characteristic

Test method

pH-Value (at 20 °C): 5,0-7,0

Changes in the physical state

Initial boiling point and boiling range:

Flash point:

-104 °C

Lower explosion limits:

1,4 vol. %

Upper explosion limits:

15 vol. %

Ignition temperature:

340 °C

Density (at 24 °C):

0,75 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The product is stable under storage at normal ambient temperatures.

Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from heat. Flame

10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents. strong alkalis

10.6. Hazardous decomposition products

Carbon dioxide (CO2). Carbon monoxide Sulphur oxides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

No data available



according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 6 of 9

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
123-54-6	acetylacetone, pentane-2,4-dione					
	oral	LD50 mg/kg	575	Rat		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	oral	LD50 mg/kg	> 5000	Rat	IUCLID	
	dermal	LD50 mg/kg	11000	Rabbit		
119-36-8	Methyl salicylate					
	oral	ATE mg/kg	500			
104-55-2	Cinnamaldehyde					
	dermal	ATE mg/kg	1100			

Irritation and corrosivity

Has degreasing effect on the skin.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

Observations relevant to classification

No data available

Other observations

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 7 of 9

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
123-54-6	acetylacetone, pentane-2,4-dione						
	Acute fish toxicity	LC50	72 mg/l		Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50	75 mg/l	48 h	Daphnia magna		
107-98-2	7-98-2 1-methoxy-2-propanol; monopropylene glycol methyl ether						
	Acute fish toxicity	LC50 10000 mg/	4600 - I	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 mg/l	> 1000		Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-54-6	acetylacetone, pentane-2,4-dione	0,4
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Remove according to the regulations.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances

Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances

Classified as hazardous waste.





according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 8 of 9

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

 14.3. Transport hazard class(es):
 2.1

 14.4. Packing group:

 Hazard label:
 2.1

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg





according to Regulation (EC) No 1907/2006

4715 Power rust dissolver, mineral oil free 250 ml

Revision date: 14.03.2017 Product code: 91616 Page 9 of 9

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

2010/75/EU (VOC): 78,2%; 600,6 g/l // 75,1%; 576,8 g/l (CH)

2004/42/EC (VOC): 78,2%; 600,6 g/l

75,1%; 576,8 g/I (CH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

EUH208 Contains Cinnamaldehyde. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)