

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2295 Rust converter professional 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive paints, containing solvents, high in aromatics

1.3. Details of the supplier of the safety data sheet

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Götz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

1.4. Emergency telephone number:

+49 761-19 240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

acetone

butan-1-ol

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)

pyrogallol

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 2 of 11

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Anti-corrosive paints, containing solvents, high in aromatics

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
115-10-6	dimethyl ether			60 - < 70 %
	204-065-8	603-019-00-8		
	Flam. Gas 1; H220			
67-64-1	acetone			10 - < 20 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
123-86-4	n-butyl acetate			5 - < 10 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
71-36-3	butan-1-ol			5 - < 10 %
	200-751-6	603-004-00-6		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
25068-38-6	epoxy resin (Mn <= 700), reaction product: bisphenol-A-(epichlorhydrin)			0.1 - < 5 %
	500-033-5	603-074-00-8		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
87-66-1	pyrogallol			0.1 - < 5 %
	201-762-9	604-009-00-6		
	Muta. 2, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 3; H341 H332 H312 H302 H412			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If unconscious place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 4 of 11

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

The following symptoms may occur: Headache. Drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, oxidizing. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 5 of 11

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles

Hand protection

Tested protective gloves must be worn.
 Suitable material: NBR (Nitrile rubber).
 Thickness of the glove material > 0,4mm
 penetration time (maximum wearing period): > 30 min.
 DIN EN 374

Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Avoid contact with skin, eyes and clothes.

Respiratory protection

Use suitable breathing apparatus. Filter type: AX (for group 1 low boilers). In case of a maximum contaminant concentration in inhaled air of 100 mL/m³ (0.01 % by vol.), group 1 may be used for a maximum of 40 min. In case of a maximum contaminant concentration in inhaled air of 500 mL/m³ (0.05 % by vol.), group 1 may be used for a maximum of 20 min.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
 Colour: clear

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 6 of 11

Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not applicable

Initial boiling point and boiling range: -24,8 °C

Flash point: -42,2 °C

Lower explosion limits: 1,2 vol. %

Upper explosion limits: 32 vol. %

Ignition temperature: 240 °C

Auto-ignition temperature > 300

 Vapour pressure:
(at 20 °C) 5102 hPa

 Density: 0,73 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

9.2. Other information

none

SECTION 10: Stability and reactivity

10.1. Reactivity

Special hazards arising from the substance or mixture. There are no data available on the mixture itself.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Pressurised container: May burst if heated. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

Reacts with : Acid. alkali. Oxidizing agents.

10.6. Hazardous decomposition products

none

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1819,5 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone				
	oral	LD50 mg/kg 5800	Rat	RTECS	
	dermal	LD50 mg/kg 20000	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
1330-20-7	xylene				
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
71-36-3	butan-1-ol				
	oral	ATE mg/kg 500			
87-66-1	pyrogallol				
	oral	ATE mg/kg 500			
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			

Irritation and corrosivity

Causes skin irritation.
Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (epoxy resin (Mn ≤ 700), reaction product: bisphenol-A-(epichlorhydrin))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (butan-1-ol)
May cause drowsiness or dizziness. (acetone; n-butyl acetate; butan-1-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience
Observations relevant to classification

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information
12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 8 of 11

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
67-64-1	acetone	-0,24

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 9 of 11

Land transport (ADR/RID)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
----------------------------	-----

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 10 of 11

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: acetone

2010/75/EU (VOC): 97%; 705 g/l

2004/42/EC (VOC): 97%; 705 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

National regulatory information

Employment restrictions: Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Acute Tox. 4; H302	Bridging principle "Aerosols"
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2295 Rust converter professional 400 ml

Revision date: 19.02.2019

Product code: 70460

Page 11 of 11

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Beschichtungsmaterial, Korrosionsschutz	-	-	-	-	-	-	-	2
2	Coatings and paints, thinners, paint removers	-	-	9a	7, 11	11a	7, 7a	91	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)