

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

3040 Nano rain repellent Eco

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Acid-hardened sealants, high in solvents

1.3. Details of the supplier of the safety data sheet

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Goetz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

1.4. Emergency telephone number: Vergiftungs-Informationen-Zentrale Freiburg
+49 761-19 240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 2 of 8

P403+P235 Store in a well-ventilated place. Keep cool.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Acid-hardened sealants, high in solvents

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64-17-5	ethanol			>85 %
	200-578-6	603-002-00-5		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder,, alcohol resistant foam, Water spray.

Unsuitable extinguishing media

Strong water jet

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Do not allow water used to extinguish fire to enter drains or waterways. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, oxidizing. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

After contact with skin, wash immediately with plenty of water and soap.

Eye/face protection

Wear eye/face protection.

DIN EN 166

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 4 of 8

Hand protection

Butyl caoutchouc (butyl rubber)
Thickness of the glove material > 0,4 mm
penetration time (maximum wearing period): 480 min
Breakthrough times and swelling properties of the material must be taken into consideration.
EN ISO 374

Skin protection

Wear antistatic work clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not allow to enter into surface water or drains. No special environmental measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	Alcohol

pH-Value:	2	Test method
-----------	---	--------------------

Changes in the physical state

Melting point:	-117 °C
Initial boiling point and boiling range:	78 °C
Flash point:	18 °C
Lower explosion limits:	3,5 vol. %
Upper explosion limits:	15 vol. %
Ignition temperature:	400 °C
Vapour pressure: (at 20 °C)	57 hPa
Density (at 20 °C):	0,82 g/cm ³ DIN 51757
Water solubility:	completely miscible
Solvent content:	90%

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.
Keep away from heat.

10.3. Possibility of hazardous reactions

Keep away from: acid. alkali. Oxidizing agents. Alkali metals. Alkaline earth metal

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 5 of 8

10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

10.5. Incompatible materials

acid. alkali. Oxidizing agents. Alkali metals. Alkaline earth metal

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

Carbon dioxide. Carbon monoxide Nitrogen oxides (NOx). Hydrogen chloride (HCl)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 6200 mg/kg	Rat	IUCLID	
	inhalation (4 h) vapour	LC50 95,6 mg/l	Rat	RTECS	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

Observations relevant to classification

May be harmful if swallowed, in contact with skin or if inhaled.

Other observations

Has degreasing effect on the skin.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 6 of 8

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol					
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

The evaluation was carried out according to the calculation method of the preparation directive.

According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 7 of 8

<u>14.1. UN number:</u>	UN 1170
<u>14.2. UN proper shipping name:</u>	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1170
<u>14.2. UN proper shipping name:</u>	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1170
<u>14.2. UN proper shipping name:</u>	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Special Provisions:	144
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	UN 1170
<u>14.2. UN proper shipping name:</u>	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Special Provisions:	A3 A58 A180
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco

Revision date: 26.06.2020

Product code: 94153

Page 8 of 8

IATA-max. quantity - Cargo:

60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: ethanol

2010/75/EU (VOC): 90 % (738 g/l)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008

[CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Acid-hardened sealants, high in solvents	IS, PW, C	-	9a, 15, 32	11, 19	8e, 10a	1, 1a, 1b, 4	7, 13, 14, 119	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)