

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

3300 Textile and leather impregnation

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Impregnating agent

1.3. Details of the supplier of the safety data sheet

Company name: KERONA GmbH
Street: Zeilbaumweg 15
Place: D-74613 Öhringen
Telephone: +49 7941-9205 4080
e-mail: mail@kerona.de
Contact person: Dr. Hans Goetz
e-mail: hans.goetz@kerona.de
Internet: www.kerona.de

Telephone: +49 170-8548 710

1.4. Emergency telephone number:

+49 761-19 240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Naphtha (petroleum) hydrotreated light

propan-2-ol

isopropyl acetate

n-butyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H222

Extremely flammable aerosol.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 2 of 9

H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Operate if possible out of doors or in a well-ventilated place.

2.3. Other hazards

Caution! Please absolutely note! May cause damage to health by inhalation! Only use outdoors or with good ventilation! Only spray for a few seconds! Large-surface leather and textile articles should only be sprayed outdoors and well ventilated! Keep out of reach of children!

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Impregnating agent

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-48-9	Naphtha (petroleum) hydrotreated heavy			25-35 %
	265-150-3			
	Asp. Tox. 1; H304			
64742-49-0	Naphtha (petroleum) hydrotreated light			2-2,5 %
	265-151-9		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
67-63-0	propan-2-ol			15-20 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
108-21-4	isopropyl acetate			0.1 - < 5 %
	203-561-1	607-024-00-6		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			0.1 - < 5 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 3 of 9

sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If unconscious place in recovery position and seek medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of breathing difficulties administer oxygen.

After contact with skin

Wash with plenty of water. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Pressurised container: May burst if heated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 4 of 9

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, oxidizing. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
108-21-4	Isopropyl acetate	200	849		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use appropriate respiratory protection. Combination filtering device (EN 14387)
Particle filter device (DIN EN 143)

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles

Hand protection

Tested protective gloves must be worn.
Suitable material: NBR (Nitrile rubber).
Thickness of the glove material > 0,4mm
penetration time (maximum wearing period): > 480 min.
EN ISO 374

Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Avoid contact with skin, eyes and clothes.

Respiratory protection

Use appropriate respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	-11,7 °C
Flash point:	-40 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	240 °C

Oxidizing properties

No data available

Vapour pressure: (at 20 °C)	2-4 bar hPa
Density (at 20 °C):	0,6775 g/cm ³
Bulk density:	No data available
Water solubility:	partially miscible
Viscosity / dynamic:	No data available
Viscosity / kinematic:	< 7 mm ² /s / 40°C (liquid) mm ² /s
Flow time:	No data available
Solvent separation test:	No data available

9.2. Other information

none

SECTION 10: Stability and reactivity

10.1. Reactivity

Special hazards arising from the substance or mixture. There are no data available on the mixture itself.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Pressurised container: May burst if heated. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

Reacts with : Oxidizing agents.

10.6. Hazardous decomposition products

Pyrolysis products, containing fluorine

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 6 of 9

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) hydrotreated light; propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

Observations relevant to classification

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 7 of 9

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1
Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1
Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1
Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 8 of 9

EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Naphtha (petroleum) hydrotreated heavy; Naphtha (petroleum) hydrotreated light

Entry 29: butane

2010/75/EU (VOC): 99,5%; 674,1 g/l

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

3300 Textile and leather impregnation

Revision date: 13.01.2020

Product code: 91169

Page 9 of 9

H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Oberflächenbehandlung	-	-	14	-	-	-	-	3

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)