

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4650 Drilling and cutting oil Spray 400 ml

UFI: TNXD-V88R-N00R-JRW8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	
e-mail:	mail@kerona.de	
Contact person:	Dr. Hans Goetz	Telephone: +49 170-8548 710
e-mail:	hans.goetz@kerona.de	
Internet:	www.kerona.de	

1.4. Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg
+49 761-19 240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.
Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger**Pictograms:**

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat. No Smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 2 of 8

2.3. Other hazards

Pressurised container: May burst if heated.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
8042-47-5	White mineral oil (petroleum)	25 - 50 %
	232-455-8	
	Asp. Tox. 1; H304	
65072-03-9	Hydrocarbons C10-C12 isoalkanes < 2% aromatics	5 - 10 %
	923-037-2	
	01-2119471991-29	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411 EUH066	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 3 of 8

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles
DIN EN 166

Hand protection

Tested protective gloves must be worn.
Suitable material: NBR (Nitrile rubber).
Thickness of the glove material > 0,45mm
penetration time (maximum wearing period): > 240 min. EN ISO 374
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: A (EN 14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	red	
Odour:	characteristic	
pH-Value:		not applicable

Changes in the physical state

Melting point:		not determined
Boiling point or initial boiling point and boiling range:		< 0 °C
Flash point:		<0 °C

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	9,4 vol. %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 5 of 8

Auto-ignition temperature:	200 °C
Density (at 20 °C):	0,65 g/cm ³
Water solubility:	Immiscible
Solvent content:	64,9%

SECTION 10: Stability and reactivity

10.1. Reactivity

Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent, strong

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

Reacts with : Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 6 of 8

SECTION 12: Ecological information

12.1. Toxicity

Do not allow to enter into surface water or drains.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Product is easily volatile.

12.5. Results of PBT and vPvB assessment

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1



Classification code: 5F

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 7 of 8

Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4650 Drilling and cutting oil Spray 400 ml

Revision date: 10.02.2021

Product code: 94225

Page 8 of 8

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 29

2010/75/EU (VOC): 64,9% (420,9 g/L)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Oberflächenbehandlung	-	-	14	-	-	-	-	3
2	Lubricating agent	PW, C	-	24	11	-	-	7, 80	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)