

according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4740 Rust dissolver MoS2 Spray 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Company name: KERONA GmbH
Street: Zeilbaumweg 15
Place: D-74613 Öhringen
Telephone: +49 7941-9205 4080
e-mail: mail@kerona.de

Contact person: Dr. Hans Goetz Telephone: +49 170-8548 710

e-mail: hans.goetz@kerona.de

Internet: www.kerona.de

1.4. Emergency telephone Poison center Freiburg (DE): +49 761-19 240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children. P210 Keep away from heat. No Smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

Pressurised container: May burst if heated.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 2 of 9

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REA	CH No		
	GHS Classification					
	Hydrocarbons C10-C13 - n-alkanes - iso-alkanes - cyclics - < 2% aromatics					
	918-481-9 01-2119457273-39					
	Asp. Tox. 1; H304					
64742-53-6	Destillates, with hydrogen treat		10 - 20 %			
	265-156-6		01-2	119480375-34		
	Asp. Tox. 1; H304					
111-76-2	2-butoxyethanol		1,0 - 2,5 %			
	203-905-0	603-014-00-0				
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
111-76-2	203-905-0	2-butoxyethanol	1,0 - 2,5 %
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = ral: LD50 = 470 mg/kg	

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation

4.3. Indication of any immediate medical attention and special treatment needed



KERONA GmbH

according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 3 of 9

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 4 of 9

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810	ĺ	STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles

DIN EN 166

Hand protection

Tested protective gloves must be worn.

Suitable material: NBR (Nitrile rubber).

Thickness of the glove material > 0,45mm

penetration time (maximum wearing period): > 240 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: A (EN 14387)





according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: grey
Odour: characteristic

pH-Value: not applicable

Changes in the physical state

Melting point: not determined Boiling point or initial boiling point and $$\rm < 0\ ^{\circ}C$$

boiling range:

Flash point: <0 °C

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits:0,6 vol. %Upper explosion limits:9,4 vol. %Auto-ignition temperature:>200 °CDensity (at 20 °C):0,69 g/cm³Water solubility:ImmiscibleSolvent content:85,5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent, strong

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon dioxide (CO2), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 6 of 9

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
111-76-2	2-butoxyethanol	2-butoxyethanol								
	oral	LD50 mg/kg	470	Rat						
	dermal	ATE mg/kg	1100							
	inhalation vapour	ATE	11 mg/l							
	inhalation aerosol	ATE	1,5 mg/l							

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

SECTION 12: Ecological information

12.1. Toxicity

Do not allow to enter into surface water or drains.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name									
	Aquatic toxicity	equatic toxicity Dose [h] [d] Species Source Method								
111-76-2	2-butoxyethanol									
	Acute fish toxicity	LC50 1490 mg/l	96 h Lepomis macrochiru	s						

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol	0,81 (25°C)

12.4. Mobility in soil

Product is easily volatile.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 7 of 9

12.5. Results of PBT and vPvB assessment

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1





according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 10.02.2021 Product code: 94226 Page 8 of 9



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

SECTION 15: Regulatory information

$\underline{\textbf{15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture}$

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29

2010/75/EU (VOC): 85,5 % 592,1 g/L)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Product code: 94226 Revision date: 10.02.2021 Page 9 of 9

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Pressurised container: May burst if heated.

Classification	Classification procedure		
Aerosol 1; H222-H229	On basis of test data		
Asp. Tox. 1; H304	Calculation method		

Re

. Tox. 1; H304		Calculation method	
Relevant H and	d EUH statements	(number and full text)	
H222	Fxtren	nely flammable aerosol.	

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

Harmful in contact with skin. H312 Causes skin irritation. H315 H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Further Information

H229

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Surface modifier	1	-	14	-	·	-	-	3
	Washing and cleaning products	IS, PW, C	-	35	7, 11, 19, 28	4, 8d	-	105	

LCS: Life cycle stages SU: Sectors of use PC: Product categories PROC: Process categories ERC: Environmental release categories AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)