

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 1 of 20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2040 Zinc spray professional 400 ml

UFI: KHQ9-U6DR-P00S-H8XQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Special finishes

1.3. Details of the supplier of the safety data sheet

Company name:	Kisling Deutschland GmbH
Street:	Salzstraße 15
Place:	D-74676 Niedernhall
Telephone:	+49 7940 5096161
E-mail:	info@kisling.com
Contact person:	Isabel Winter Telephone: +49 7941 92054087
E-mail:	info@kisling.com
Internet:	www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H335
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

xylene
Titanium tetrabutanolat
Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics
ethylbenzene

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 2 of 20

H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

Tactile warning according to EN/ISO 11683.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H318-H332-H335-H336-H373

Precautionary statements

P102-P210-P211-P251-P280-P410+P412

2.3. Other hazards

Wassergefährdungsklasse 3 - stark wassergefährdend

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 3 of 20

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1330-20-7	xylene			15 - < 30 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
5593-70-4	Titanium tetrabutanolate			5 - < 15 %
	227-006-8		01-2119967423-33	
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336			
7440-66-6	zinc powder - zinc dust (stabilised)			5 - < 15 %
	231-175-3	030-001-01-9		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics			5 - < 15 %
	927-510-4			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane			5 - < 15 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons C6-C7 - isoalkanes - cyclics - <5% n-hexane			5 - < 15 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
	Hydrocarbons C6 - isoalkanes <5% n-hexane			5 - < 15 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
100-41-4	ethylbenzene			1 - < 5 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
64742-48-9	Naphtha (petroleum) hydrotreated heavy			1 - < 5 %
	265-150-3			
	Asp. Tox. 1; H304			
78-78-4	isopentane			0.1 - < 1 %
	201-142-8	601-085-00-2		
	Flam. Liq. 1, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H224 H336 H304 H411 EUH066			
110-54-3	n-hexane			0.1 - < 1 %
	203-777-6	601-037-00-0		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			
108-88-3	toluene			0.1 - < 1 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			
110-82-7	cyclohexane			0.1 - < 1 %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 4 of 20

	203-806-2	601-017-00-1	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	15 - < 30 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 4300 mg/kg	
5593-70-4	227-006-8	Titanium tetrabutanolat	5 - < 15 %
		oral: LD50 = > 2000 mg/kg	
7440-66-6	231-175-3	zinc powder - zinc dust (stabilised)	5 - < 15 %
		oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
64742-49-0	927-510-4	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics	5 - < 15 %
		inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >5840 mg/kg	
64742-49-0	921-024-6	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane	5 - < 15 %
		inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
	931-254-9	Hydrocarbons C6 - isoalkanes <5% n-hexane	5 - < 15 %
		inhalation: LC50 = 73860 mg/l (vapours)	
100-41-4	202-849-4	ethylbenzene	1 - < 5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); oral: LD50 = ca. 3500 mg/kg	
64742-48-9	265-150-3	Naphtha (petroleum) hydrotreated heavy	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
110-54-3	203-777-6	n-hexane	0.1 - < 1 %
		inhalation: LC50 = 73860 mg/l (vapours); dermal: LD50 = > 2000 mg/kg STOT RE 2; H373: >= 5 - 100	
108-88-3	203-625-9	toluene	0.1 - < 1 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	
110-82-7	203-806-2	cyclohexane	0.1 - < 1 %
		inhalation: LC50 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). First aider: Pay attention to self-protection! Never give anything by mouth to an unconscious person or a person with cramps. Take off immediately all contaminated clothing.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Medical treatment necessary.

After contact with eyes

Protect uninjured eye. Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 5 of 20

an ophthalmologist.

After ingestion

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not inhale explosion and combustion gases. Heating causes rise in pressure with risk of bursting.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. When using do not eat or drink. Wash hands before breaks and after work. Draw up and observe skin protection programme.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 6 of 20

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
110-82-7	Cyclohexane	200	700		TWA (8 h)	
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
78-78-4	Isopentane	1000	3000		TWA (8 h)	
110-54-3	n-Hexane	20	72		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 7 of 20

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m ³
Worker DNEL, acute		inhalation	systemic	442 mg/m ³
Worker DNEL, long-term		inhalation	local	221 mg/m ³
Worker DNEL, acute		inhalation	local	442 mg/m ³
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m ³
Consumer DNEL, acute		inhalation	systemic	260 mg/m ³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m ³
Consumer DNEL, acute		inhalation	local	260 mg/m ³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day
5593-70-4	Titanium tetrabutanolate			
Worker DNEL, long-term		inhalation	systemic	127 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	152 mg/m ³
Consumer DNEL, long-term		dermal	systemic	37,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	3,75 mg/kg bw/day
7440-66-6	zinc powder - zinc dust (stabilised)			
Worker DNEL, long-term		inhalation	systemic	5 mg/m ³
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m ³
Consumer DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,83 mg/kg bw/day
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m ³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
	Hydrocarbons C6 - isoalkanes <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	5306 mg/m ³
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1131 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 8 of 20

Consumer DNEL, long-term	dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1301 mg/kg bw/day
100-41-4	ethylbenzene		
Worker DNEL, long-term	inhalation	systemic	77 mg/m ³
Worker DNEL, acute	inhalation	local	293 mg/m ³
Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	15 mg/m ³
Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
64742-48-9	Naphtha (petroleum) hydrotreated heavy		
Worker DNEL, long-term	inhalation	systemic	1,9 mg/m ³
Worker DNEL, acute	inhalation	systemic	1286,4 mg/m ³
Worker DNEL, long-term	inhalation	local	837,5 mg/m ³
Worker DNEL, acute	inhalation	local	1066,67 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	0,41 mg/m ³
Consumer DNEL, acute	inhalation	systemic	1152 mg/m ³
Consumer DNEL, long-term	inhalation	local	178,57 mg/m ³
Consumer DNEL, acute	inhalation	local	640 mg/m ³
110-54-3	n-hexane		
Worker DNEL, long-term	inhalation	systemic	75 mg/m ³
Worker DNEL, long-term	dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	16 mg/m ³
Consumer DNEL, long-term	dermal	systemic	5,3 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
108-88-3	toluene		
Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
Worker DNEL, acute	inhalation	systemic	384 mg/m ³
Worker DNEL, long-term	inhalation	local	192 mg/m ³
Worker DNEL, acute	inhalation	local	384 mg/m ³
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m ³
Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
Consumer DNEL, long-term	inhalation	local	56,5 mg/m ³
Consumer DNEL, acute	inhalation	local	226 mg/m ³
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
110-82-7	cyclohexane		
Worker DNEL, long-term	inhalation	systemic	700 mg/m ³
Worker DNEL, acute	inhalation	systemic	1400 mg/m ³
Worker DNEL, long-term	inhalation	local	700 mg/m ³
Worker DNEL, acute	inhalation	local	1400 mg/m ³
Worker DNEL, long-term	dermal	systemic	2016 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 9 of 20

Consumer DNEL, long-term	inhalation	systemic	206 mg/m ³
Consumer DNEL, acute	inhalation	systemic	412 mg/m ³
Consumer DNEL, long-term	inhalation	local	206 mg/m ³
Consumer DNEL, acute	inhalation	local	412 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1186 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	59,4 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 10 of 20

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
5593-70-4	Titanium tetrabutanolate	
Freshwater		0,08 mg/l
Freshwater (intermittent releases)		2,25 mg/l
Marine water		0,008 mg/l
Freshwater sediment		0,069 mg/kg
Marine sediment		0,007 mg/kg
Micro-organisms in sewage treatment plants (STP)		65 mg/l
Soil		0,017 mg/kg
7440-66-6	zinc powder - zinc dust (stabilised)	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		121 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,1 mg/l
Soil		106,8 mg/kg
100-41-4	ethylbenzene	
Freshwater		0,1 mg/l
Freshwater (intermittent releases)		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		13,7 mg/kg
Marine sediment		1,37 mg/kg
Secondary poisoning		20 mg/kg
Micro-organisms in sewage treatment plants (STP)		9,6 mg/l
Soil		2,68 mg/kg
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 11 of 20

110-82-7	cyclohexane	
Freshwater		0,0447 mg/l
Freshwater (intermittent releases)		0,009 mg/l
Marine water		0,00447 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		0,36 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,24 mg/l
Soil		0,694 mg/kg

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Hand protection Viton. > 240 min

Skin protection

Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	silver grey
Odour:	characteristic
Boiling point or initial boiling point and boiling range:	-42 °C
Lower explosion limits:	1,0 vol. %
Upper explosion limits:	9,4 vol. %
Flash point:	-104 °C
Auto-ignition temperature:	300 °C
Water solubility:	unlöslich
Vapour pressure:	3.300 hPa
Density (at 20 °C):	0,757 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product develops hydrogen in an aqueous solution in contact with metals.

10.3. Possibility of hazardous reactions

Does not decompose when used for intended uses. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 12 of 20

10.5. Incompatible materials

Materials to avoid: Acid, alkali.

10.6. Hazardous decomposition products

Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) 0.0000 mg/kg; ATE (inhalation vapour) 0.0000 mg/l; ATE (inhalation dust/mist) 0.0000 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 13 of 20

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 mg/kg	4300	Rat	
	dermal	LD50 mg/kg	2000	Rabbit	
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1.5 mg/l		
5593-70-4	Titanium tetrabutanolat				
	oral	LD50 mg/kg	> 2000	Rat	Study report (2013) OECD Guideline 423
7440-66-6	zinc powder - zinc dust (stabilised)				
	oral	LD50 mg/kg	> 2000	Rat	Study report (1996) OECD Guideline 401
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics				
	oral	LD50 mg/kg	>5840	Rat	
	dermal	LD50 mg/kg	> 2800 - 3100	Rat	Study report (1977) The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 mg/l	> 23,3	Rat	Study report (1988) OECD Guideline 403
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane				
	oral	LD50 mg/kg	>5000	Rat	OECD 401
	dermal	LD50 mg/kg	>2000	Rat	OECD 402
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat	OECD 403
	Hydrocarbons C6 - isoalkanes <5% n-hexane				
	inhalation (4 h) vapour	LC50 mg/l	73860	Rat	Industrial Medicine, Vol. 39, No. 5, May OECD Guideline 403
100-41-4	ethylbenzene				
	oral	LD50 mg/kg	ca. 3500	Rat	AMA Arch. Ind. Health. 14:387-398. (1956) No guideline available
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1.5 mg/l		
64742-48-9	Naphtha (petroleum) hydrotreated heavy				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1986) OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1986) OECD Guideline 402
110-54-3	n-hexane				
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)
	inhalation (4 h) vapour	LC50 mg/l	73860	Rat	Industrial Medicine, Vol. 39, No. 5, May OECD Guideline 403
108-88-3	toluene				
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975) EU Method B.1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 14 of 20

	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
110-82-7	cyclohexane					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 mg/l	> 5540	Rat	Study report (1981)	OECD Guideline 403

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene; Titanium tetrabutanolate)

May cause drowsiness or dizziness. (Titanium tetrabutanolate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 15 of 20

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1330-20-7	xylene					
	Fish toxicity	NOEC > 1,3 mg/l	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC 1,17 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(EC50 > 175 mg/l)	0 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (OECD Guideline 209
5593-70-4	Titanium tetrabutanolate					
	Acute fish toxicity	LC50 1740 mg/l	96 h	Pimephales promelas	Aquatic Toxicology and Hazard Assessment	other: test methods described by the U.S
	Acute algae toxicity	ErC50 225 mg/l	96 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EC50 1300 mg/l	48 h	Daphnia magna	Environmental Toxicology and Chemistry,	other: ASTM 1984: Standard E729-80 and A
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
	Hydrocarbons C6 - isoalkanes <5% n-hexane					
	Acute fish toxicity	LL50 18,27 mg/l	96 h	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute algae toxicity	ErC50 13,56 mg/l	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EL50 31,9 mg/l	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC 4,089 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 7,138 mg/l	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicol. Environ. Saf. 16:158-169 (19	OECD Guideline 203

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 16 of 20

	Acute algae toxicity	ErC50	4,6 mg/l	72 h	Pseudokirchneriella subcapitata	Chemosphere 10(10): 1123-1126 (1981)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	1,8 - 2,4	48 h	Daphnia magna	Water Res. 27:903-909 (1993)	other: According to EPA method F
	Acute bacteria toxicity	(EC50 mg/l)	ca. 600	0.5 h	activated sludge, domestic	Study report (1988)	OECD Guideline 209
64742-48-9	Naphtha (petroleum) hydrotreated heavy						
	Acute fish toxicity	LL50	8,2 mg/l	96 h	Pimephales promelas	Study report (1995)	other: EPA 66013-75-009
	Acute algae toxicity	ErC50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50	4,5 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
	Fish toxicity	NOEC	2,6 mg/l	21 d	Daphnia magna	Study report (1999)	other: OECD Guideline 211
	Crustacea toxicity	NOEC	2,6 mg/l	21 d	Daphnia magna	Study report (1999)	OECD Guideline 211
110-54-3	n-hexane						
	Acute fish toxicity	LL50 mg/l	12,51	96 h	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute algae toxicity	ErC50 mg/l	9,285	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EL50 mg/l	21,85	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC	2,8 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	4,888	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
108-88-3	toluene						
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
110-82-7	cyclohexane						
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Raphidocelis subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987)	OECD Guideline 202

12.2. Persistence and degradability

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 17 of 20

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3,2
5593-70-4	Titanium tetrabutanolat	0,84
	Hydrocarbons C6 - isoalkanes <5% n-hexane	3,6
100-41-4	ethylbenzene	3,6
110-54-3	n-hexane	4
108-88-3	toluene	2,73
110-82-7	cyclohexane	3,44

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
7440-66-6	zinc powder - zinc dust (stabilised)	69,48	Capoeta fusca	Water Qual Expo Heal
	Hydrocarbons C6 - isoalkanes <5% n-hexane	501,187	Pimephales promelas	QSAR in Environmenta
100-41-4	ethylbenzene	1	Oncorhynchus kisutch	Arch. Environ. Conta
110-54-3	n-hexane	501,187	Pimephales promelas	QSAR in Environmenta
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

Wassergefährdungsklasse 3 - stark wassergefährdend

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 18 of 20

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste


Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)


14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)


14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Safety Data Sheet

according to Regulation (EC) No 1907/2006


2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 19 of 20

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
	
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 48, Entry 57, Entry 75

2010/75/EU (VOC): 85%; 640 g/l

2004/42/EC (VOC): 640 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

National regulatory information

Employment restrictions: Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

Aerosol: Aerosols
Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2040 Zinc spray professional 400 ml

Revision date: 01.02.2023

Product code: 70672

Page 20 of 20

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Acute Tox. 4; H332	Bridging principle "Aerosols"
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Coatings and paints, thinners, paint removers	-	-	9a	7, 11	11a	7, 7a	91	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)