

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 1 of 16

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

2250 Paint primer white grey 400 ml

UFI: M835-Y8GA-A00R-7XVC

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Primers

### 1.3. Details of the supplier of the safety data sheet

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	
E-mail:	mail@kerona.de	
Contact person:	Isabel Winter	Telephone: +49 7941 9205 4087
E-mail:	isabel.winter@kerona.de	
Internet:	www.kerona.de	

### 1.4. Emergency telephone number:

Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Aerosol 1; H222-H229  
Self-react. E; H242  
Skin Irrit. 2; H315  
Eye Dam. 1; H318  
STOT SE 3; H335  
STOT SE 3; H336  
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

n-butyl acetate  
xylene  
butan-1-ol

Signal word:

Danger

Pictograms:



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H242	Heating may cause a fire.
H315	Causes skin irritation.
H318	Causes serious eye damage.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 2 of 16

- |      |  |
|------|--|
| H335 | May cause respiratory irritation.                                  |
| H336 | May cause drowsiness or dizziness.                                 |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

#### Precautionary statements

- |           |  |
|-----------|--|
| P102      | Keep out of reach of children.   |
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211      | Do not spray on an open flame or other ignition source.  |
| P251      | Do not pierce or burn, even after use.   |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.                   |

#### Special labelling of certain mixtures

Restricted to professional users.

#### Additional advice on labelling

Tactile warning according to EN/ISO 11683.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H222-H229-H318-H335-H336-H373

#### Precautionary statements

P102-P210-P211-P251-P410+P412

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Paints and varnishes

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 3 of 16

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
115-10-6	dimethyl ether			40 - 60 %
	204-065-8	603-019-00-8		
	Flam. Gas 1; H220			
123-86-4	n-butyl acetate			5 - < 15 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
1330-20-7	xylene			5 - < 15 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
71-36-3	butan-1-ol			1 - < 5 %
	200-751-6	603-004-00-6		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
108-65-6	2-methoxy-1-methylethyl acetate			1 - < 5 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
115-10-6	204-065-8	dimethyl ether	40 - 60 %
		inhalation: LC50 = 164000 ppm (gases)	
123-86-4	204-658-1	n-butyl acetate	5 - < 15 %
		oral: LD50 = 14130 mg/kg	
1330-20-7	215-535-7	xylene	5 - < 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 4300 mg/kg	
71-36-3	200-751-6	butan-1-ol	1 - < 5 %
		dermal: LD50 = 3400 mg/kg; oral: LD50 = 790 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 6190 - 10000 mg/kg	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

##### After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If unconscious but breathing normally, place in recovery position and seek medical advice.

##### After contact with skin

Wash with plenty of water. In case of skin irritation, consult a physician.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2250 Paint primer white grey 400 ml**

Revision date: 22.02.2023

Product code: 91390

Page 4 of 16

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

The following symptoms may occur: Dizziness.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>), Dry extinguishing powder, Foam.**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

In case of fire and/or explosion do not breathe fumes.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2250 Paint primer white grey 400 ml**

Revision date: 22.02.2023

Product code: 91390

Page 5 of 16

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

**Hints on joint storage**

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep away from heat.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limit values**

CAS No	Name of agent	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
108-65-6	2-Methoxy-1-methylethylacetate	50	275		TWA (8 h)	
		100	550		STEL (15 min)	
115-10-6	Dimethylether	1000	1920		TWA (8 h)	
123-86-4	n-Butylacetate	50	241		TWA (8 h)	EU
		150	723		STEL (15 min)	EU
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 6 of 16

### DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
115-10-6	dimethyl ether			
Worker DNEL, long-term		inhalation	systemic	1894 mg/m³
Consumer DNEL, long-term		inhalation	systemic	471 mg/m³
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	300 mg/m³
Worker DNEL, acute		inhalation	systemic	600 mg/m³
Worker DNEL, long-term		inhalation	local	300 mg/m³
Worker DNEL, acute		inhalation	local	600 mg/m³
Worker DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35,7 mg/m³
Consumer DNEL, acute		inhalation	systemic	300 mg/m³
Consumer DNEL, long-term		inhalation	local	35,7 mg/m³
Consumer DNEL, acute		inhalation	local	300 mg/m³
Consumer DNEL, long-term		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m³
Worker DNEL, acute		inhalation	systemic	442 mg/m³
Worker DNEL, long-term		inhalation	local	221 mg/m³
Worker DNEL, acute		inhalation	local	442 mg/m³
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m³
Consumer DNEL, acute		inhalation	systemic	260 mg/m³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m³
Consumer DNEL, acute		inhalation	local	260 mg/m³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day
71-36-3	butan-1-ol			
Worker DNEL, long-term		inhalation	local	310 mg/m³
Consumer DNEL, long-term		inhalation	systemic	55,357 mg/m³
Consumer DNEL, long-term		inhalation	local	155 mg/m³
Consumer DNEL, long-term		dermal	systemic	3,125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,562 mg/kg bw/day
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term		inhalation	systemic	275 mg/m³

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2250 Paint primer white grey 400 ml**

Revision date: 22.02.2023

Product code: 91390

Page 7 of 16

Worker DNEL, acute	inhalation	local	550 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	796 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	33 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	33 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	320 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	36 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 8 of 16

#### PNEC values

CAS No	Name of agent	
Environmental compartment		Value
115-10-6	dimethyl ether	
Freshwater		0,155 mg/l
Freshwater (intermittent releases)		1,549 mg/l
Marine water		0,016 mg/l
Freshwater sediment		0,681 mg/kg
Marine sediment		0,069 mg/kg
Micro-organisms in sewage treatment plants (STP)		160 mg/l
Soil		0,045 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Freshwater (intermittent releases)		0,36 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,098 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,09 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
71-36-3	butan-1-ol	
Freshwater		0,082 mg/l
Freshwater (intermittent releases)		2,25 mg/l
Marine water		0,008 mg/l
Freshwater sediment		0,324 mg/kg
Marine sediment		0,032 mg/kg
Micro-organisms in sewage treatment plants (STP)		2476 mg/l
Soil		0,017 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Freshwater (intermittent releases)		6,35 mg/l
Marine water		0,064 mg/l
Freshwater sediment		3,29 mg/kg
Marine sediment		0,329 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,29 mg/kg

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 9 of 16

#### 8.2. Exposure controls

##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles

##### Hand protection

Tested protective gloves must be worn.

Suitable material:

Thickness of the glove material > 0,4mm

> 30 min.

EN ISO 374

##### Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Avoid contact with skin, eyes and clothes.

##### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: AP2 (EN 140/143).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	light grey, red brown
Odour:	characteristic

#### Test method

Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	not applicable
Lower explosion limits:	0,9 vol. %
Upper explosion limits:	14 vol. %
Flash point:	< 21 °C
Auto-ignition temperature:	not determined
pH-Value:	not applicable
Water solubility:	practically insoluble
Vapour pressure:	> 5000 hPa
(at 50 °C)	
Density:	0,6-0,8 g/cm³

### 9.2. Other information

#### Information with regard to physical hazard classes

Self-ignition temperature >300°C

#### Other safety characteristics

Flow time: < 40s 6 DIN EN ISO 2431

#### Further Information

none

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Special hazards arising from the substance or mixture. There are no data available on the mixture itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 10 of 16

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No data available

#### 10.4. Conditions to avoid

Pressurised container: May burst if heated. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

#### 10.5. Incompatible materials

alkali.

#### 10.6. Hazardous decomposition products

none

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

No data available

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) 0.0000 mg/kg; ATE (dermal) 0.0000 mg/kg; ATE (inhalation vapour) 0.0000 mg/l; ATE (inhalation dust/mist) 0.0000 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
115-10-6	dimethyl ether				
	inhalation (4 h) gas	LC50 ppm	164000	Rat	Study report (1979)
					Ten male rats were administered the test
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg	14130	Rat	Publication (1954)
					acute oral toxicity test
1330-20-7	xylene				
	oral	LD50 mg/kg	4300	Rat	
	dermal	LD50 mg/kg	2000	Rabbit	
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1.5 mg/l		
71-36-3	butan-1-ol				
	oral	LD50 mg/kg	790	Rat	
	dermal	LD50 mg/kg	3400	Rabbit	
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 mg/kg	6190 - 10000	Rat	Study report (1985)
					OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1985)
					OECD Guideline 402

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**2250 Paint primer white grey 400 ml**

Revision date: 22.02.2023

Product code: 91390

Page 11 of 16

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness. (n-butyl acetate)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 12: Ecological information****12.1. Toxicity**

No data available

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
115-10-6	dimethyl ether					
	Acute fish toxicity	LC50 > 4100 mg/l	96 h	Poecilia reticulata	Study report (1988)	other: NEN 6504 Water - Determination of
	Acute algae toxicity	ErC50 154,917 mg/l	96 h	green algae	Other company data (2009)	other: Data generated using ECOSAR v1.00
	Acute crustacea toxicity	EC50 > 4400 mg/l	48 h	Daphnia magna	Study report (1988)	other: NEN6501: Water -Determination of
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 18 mg/l	96 h	Pimephales promelas	Publication (1984)	OECD Guideline 203
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia sp.	Publication (1959)	OECD Guideline 202
	Crustacea toxicity	NOEC 23,2 mg/l	21 d	Daphnia magna	Study report (2000)	OECD Guideline 211
1330-20-7	xylene					
	Fish toxicity	NOEC > 1,3 mg/l	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC 1,17 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(EC50 > 175 mg/l)	0 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (	OECD Guideline 209
71-36-3	butan-1-ol					
	Acute fish toxicity	LC50 1376 mg/l	96 h	Pimephales promelas	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 225 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 1328 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC 4,1 mg/l	21 d	Daphnia magna	Study report (1996)	OECD Guideline 211
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 100 - 180 mg/l	96 h	Oncorhynchus mykiss	Study report (1987)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	96 h	Raphidocelis subcapitata	Study report (1986)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	Study report (1987)	EU Method C.2
	Fish toxicity	NOEC 47,5 mg/l	14 d	Oryzias latipes	Study report (1998)	OECD Guideline 204
	Crustacea toxicity	NOEC >= 100 mg/l	21 d	Daphnia magna	Study report (1998)	OECD Guideline 211

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 13 of 16

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,07
123-86-4	n-butyl acetate	200
1330-20-7	xylene	3,2
71-36-3	butan-1-ol	10
108-65-6	2-methoxy-1-methylethyl acetate	1,2

#### BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
71-36-3	butan-1-ol	3,16		QSAR (2017)

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No data available

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

##### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 14 of 16

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Transport category: 2  
 Tunnel restriction code: D

#### Other applicable information (land transport)

E0

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L

#### Other applicable information (inland waterways transport)

E0

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: See SP277  
 EmS: F-D, S-U

#### Other applicable information (marine transport)

E0

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
 Hazard label: 2.1



Special Provisions: A145 A167 A802

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 15 of 16

Limited quantity Passenger:	30 kg G	
IATA-packing instructions - Passenger:		203
IATA-max. quantity - Passenger:		75 kg
IATA-packing instructions - Cargo:		203
IATA-max. quantity - Cargo:		150 kg

#### Other applicable information (air transport)

E0

: Y203

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 80,8%; 678 g/l

2004/42/EC (VOC): 678 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

##### National regulatory information

Employment restrictions: Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Flam. Liq: Flammable liquid

Self-react: Self-reactive substance or mixture

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 2250 Paint primer white grey 400 ml

Revision date: 22.02.2023

Product code: 91390

Page 16 of 16

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Self-react. E; H242	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

#### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Coatings and paints, thinners, paint removers	-	-	9a	7, 11	11a	7, 7a	91	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*