

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3050 Nano rain repellent longlife**

Revision date: 01.02.2023

Product code: 90178

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

3050 Nano rain repellent longlife

UFI: C6R1-H8X6-300Y-H6M5

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

Company name:	KERONA GmbH	
Street:	Zeilbaumweg 15	
Place:	D-74613 Öhringen	
Telephone:	+49 7941-9205 4080	
E-mail:	mail@kerona.de	
Contact person:	Isabel Winter	Telephone: +49 7941 9205 4087
E-mail:	isabel.winter@kerona.de	
Internet:	www.kerona.de	

**1.4. Emergency telephone number:** Medicines & Poisons Info Office +356 2545 6508

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225  
Eye Irrit. 2; H319  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

propan-2-ol

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P403+P235	Store in a well-ventilated place. Keep cool.

**Additional advice on labelling**

Tactile warning according to EN/ISO 11683.

**Labelling of packages where the contents do not exceed 125 ml****Signal word:** Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 01.02.2023

Product code: 90178

Page 2 of 10

#### Pictograms:



#### Hazard statements

H336

#### Precautionary statements

P102-P271

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Acid-hardened sealants, high in solvents

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol			50 - 100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	propan-2-ol	50 - 100 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13900 mg/kg; oral: LD50 = 4570-5840 mg/kg		

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3050 Nano rain repellent longlife**

Revision date: 01.02.2023

Product code: 90178

Page 3 of 10

**Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>), Dry extinguishing powder,, alcohol resistant foam, Water spray.**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

After contact with skin, wash immediately with plenty of water and soap.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

**Hints on joint storage**

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep away from heat.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 01.02.2023

Product code: 90178

Page 4 of 10

#### DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day

#### PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
67-63-0	propan-2-ol	
Freshwater	140,9 mg/l	
Freshwater (intermittent releases)	140,9 mg/l	
Marine water	140,9 mg/l	
Freshwater sediment	552 mg/kg	
Marine sediment	552 mg/kg	
Secondary poisoning	160 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2251 mg/l	
Soil	28 mg/kg	

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

rubber gloves.

Thickness of the glove material > 0,4 mm

> 480 min

Breakthrough times and swelling properties of the material must be taken into consideration.

##### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

##### Environmental exposure controls

Do not allow to enter into surface water or drains. No special environmental measures are necessary.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	Alcohol

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3050 Nano rain repellent longlife**

Revision date: 01.02.2023

Product code: 90178

Page 5 of 10

Boiling point or initial boiling point and boiling range:	82 °C
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Flash point:	12 °C
Auto-ignition temperature:	425 °C
pH-Value:	2,5
Vapour pressure:	46,51 hPa
(at 20 °C)	
Density (at 20 °C):	0,79 g/cm <sup>3</sup>

**9.2. Other information****Other safety characteristics**

Solvent content:	> 75
Viscosity / dynamic:	2,78 mPa·s
(at 20 °C)	

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No data available

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Keep away from: alkali.

**10.4. Conditions to avoid**

Thermal decomposition can lead to the escape of irritating gases and vapours.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

**10.5. Incompatible materials**

No data available

**10.6. Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapours.

Carbon monoxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 01.02.2023

Product code: 90178

Page 6 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol				
	oral	LD50 4570-5840 mg/kg	Rat	Pre-supplier/manufacturer	OECD 401
	dermal	LD50 13900 mg/kg	Rabbit	Pre-supplier/manufacturer	OECD 402
	inhalation (4 h) vapour	LC50 30 mg/l	Rat	Pre-supplier/manufacturer	

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

### 11.2. Information on other hazards

#### Other information

Has degreasing effect on the skin.

#### Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 12: Ecological information

### 12.1. Toxicity

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol					
	Acute fish toxicity	LC50 10000 mg/l	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203

### 12.2. Persistence and degradability

Some of the components are poorly biodegradable.

### 12.3. Bioaccumulative potential

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 01.02.2023

Product code: 90178

Page 7 of 10

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

The evaluation was carried out according to the calculation method.

According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains.

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

##### Contaminated packaging

Non-contaminated packages may be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 1219

##### 14.2. UN proper shipping name:

ISOPROPANOL (ISOPROPYL ALCOHOL)

##### 14.3. Transport hazard class(es):

3

##### 14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 01.02.2023

Product code: 90178

Page 8 of 10

Special Provisions: 601  
Limited quantity: 1 L  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

#### Other applicable information (land transport)

E2

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Special Provisions: 601  
Limited quantity: 1 L

#### Other applicable information (inland waterways transport)

E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: -  
Limited quantity: 1 L  
EmS: F-E, S-D

#### Other applicable information (marine transport)

E2

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: A180  
Limited quantity Passenger: 1 L  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3050 Nano rain repellent longlife

Revision date: 01.02.2023

Product code: 90178

Page 9 of 10

#### Other applicable information (air transport)

E2

: Y341

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 99,7%; 787,6 g/l

##### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

### SECTION 16: Other information

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

#### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Acid-hardened sealants, high in solvents	IS, PW, C	-	9a, 15, 32	11, 19	8e, 10a	1, 1a, 1b, 4	7, 13, 14, 119	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **3050 Nano rain repellent longlife**

Revision date: 01.02.2023

Product code: 90178

Page 10 of 10

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*