Telephone: +49 7941 92054087



Safety Data Sheet

according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Product code: 70634 Revision date: 07.08.2023 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4700 MultiOil Spray EV

G8M9-M65P-100Y-D9T8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Company name: Kisling Deutschland GmbH

Street: Salzstraße 15 Place: D-74676 Niedernhall +49 7940 5096161 Telephone: E-mail: info@kisling.com Contact person: Isabel Winter

E-mail: info@kisling.com

Internet: www.kisling.com

24 hr. emergency phone number +1 872 5888271 (KAR) 1.4. Emergency telephone

Medicines & Poisons Info Office +356 2545 6508 number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics - <2% aromatics

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 2 of 13

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH208 Contains Pentane-2,3-dione, Piperonal. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

C9-10 AROMATIC HYDROCARBONS

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	1272/2008)	•			
	Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics - <2% aromatics					
	927-241-2		01-2119471843-32			
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1, Aquatic Chronic 3; H226 H336 H	304 H412			
	Hydrocarbons C10-C13 - n-alkanes	s - iso-alkanes - cyclics - < 2% aroma	atics	5 - < 15 %		
	918-481-9		01-2119457273-39			
	Asp. Tox. 1; H304					
	Calcium alkylnaphthalenesulfonate	1 - < 5 %				
	939-717-7		01-2119980985-16			
	Skin Irrit. 2, Eye Irrit. 2; H315 H319					
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-		0.1 - < 1 %			
	202-414-9					
	Acute Tox. 4, Skin Corr. 1C, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H373 H400 H410					
110-25-8	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine					
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 3; H332 H315 H318 H400 H412					
120-57-0	Piperonal		0.1 - < 1 %			
	204-409-7		01-2119983608-21			
	Skin Sens. 1B; H317					
600-14-6	Pentane-2,3-dione			0.1 - < 1 %		
	209-984-8					
	Flam. Liq. 2, Skin Irrit. 2, Eye Dam.	H315 H318 H317 H373				

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc. Limits, M-factors and ATE							
	927-241-2	Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics - <2% aromatics	15 - < 30 %					
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 15000 mg/kg						
	918-481-9	Hydrocarbons C10-C13 - n-alkanes - iso-alkanes - cyclics - < 2% aromatics	5 - < 15 %					
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg							
95-38-5	202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	0.1 - < 1 %					
	oral: LD50 = 1265 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1							
110-25-8		(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	0.1 - < 1 %					
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists) Aquatic Acute 1; H400: M=1							
120-57-0	204-409-7	Piperonal	0.1 - < 1 %					
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = 2700 mg/kg							

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up





according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 4 of 13

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately.

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 5 of 13

DNEL/DMEL values

CAS No	Name of agent							
DNEL type		Exposure route	Effect	Value				
	Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics -	cyclics - <2% aromatics						
Consumer DN	EL, long-term	oral	systemic	46 mg/kg bw/day				
Worker DNEL,	long-term	dermal	systemic	77 mg/kg bw/day				
Consumer DN	EL, long-term	dermal	systemic	46 mg/kg bw/day				
Worker DNEL,	long-term	inhalation	systemic	871 mg/m³				
Consumer DN	EL, long-term	inhalation	systemic	185 mg/m³				
	Calcium alkylnaphthalenesulfonate							
Worker DNEL,	long-term	inhalation	systemic	70 mg/m³				
Worker DNEL,	long-term	dermal	systemic	10 mg/kg bw/day				
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol							
Worker DNEL,	long-term	dermal	systemic	0,06 mg/kg bw/day				
Worker DNEL,	long-term	inhalation	systemic	0,46 mg/m³				
Worker DNEL,	acute	dermal	systemic	2 mg/kg bw/day				
Worker DNEL,	acute	inhalation	systemic	14 mg/m³				
120-57-0	Piperonal							
Worker DNEL,	long-term	inhalation	systemic	5,29 mg/m³				
Worker DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day				
Consumer DN	EL, long-term	inhalation	systemic	1,3 mg/m³				
Consumer DN	EL, long-term	dermal	systemic	0,375 mg/kg bw/day				
Consumer DN	EL, long-term	oral	systemic	0,375 mg/kg bw/day				



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 6 of 13

PNEC values

CAS No	Name of agent				
Environmen	tal compartment	Value			
	Calcium alkylnaphthalenesulfonate				
Freshwater		0,004 mg/l			
Freshwater	(intermittent releases)	0,0027 mg/l			
Marine wate	er	0,0004 mg/l			
Freshwater	sediment	69 mg/kg			
Marine sedi	ment	6,9 mg/kg			
Secondary _I	poisoning	22,2 mg/kg			
Micro-organ	isms in sewage treatment plants (STP)	10 mg/l			
Soil		13,9 mg/kg			
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
Freshwater		0,00003 mg/l			
Marine wate	er	0,000003 mg/l			
Freshwater	sediment	0,376 mg/kg			
Marine sedi	farine sediment				
Micro-organ	isms in sewage treatment plants (STP)	0,27 mg/l			
Soil		0,075 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

No data available

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NR (natural rubber, Natural latex) > 0,4 mm, Breakthrough time: > 480 min EN ISO 374

Skin protection

Wear suitable protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Use suitable breathing apparatus. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light yellow
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

-42 °C

boiling range:



according to Regulation (EC) No 1907/2006

4700 MultiOil S	pray EV	
-----------------	---------	--

Revision date: 07.08.2023 Product code: 70634 Page 7 of 13

Lower explosion limits:

Upper explosion limits:

9,6 vol. %

Flash point:

-104 °C

Auto-ignition temperature:

Water solubility:

The study does not need to be conducted because the substance is known to be insoluble in water.

Density (at 20 °C):

0,66 q/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermic reaction with: Alkali (lye); Strong acid; Oxidising agent, strong

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5. Incompatible materials

Oxidising agent, strong. . Alkali (lye)

10.6. Hazardous decomposition products

Hazardous decomposition products: Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 8 of 13

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
	Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics - <2% aromatics							
	oral	LD50 mg/kg	> 15000	Rat	Study report (1977)	OECD Guideline 401		
	dermal LD50 > 5000 Rabbit Study report (1993)		Study report (1993)	OECD Guideline 402				
	Hydrocarbons C10-C13	3 - n-alkanes	- iso-alkanes	- cyclics - < 2% aron	natics			
	oral	LD50 mg/kg	> 5000	Rat	Study report (1988)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1989)	OECD Guideline 402		
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol							
	oral	LD50 mg/kg	1265	Rat		OECD 401		
110-25-8	(Z)-N-methyl-N-(1-oxo-	9-octadecen	yl)glycine					
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1.5 mg/l					
120-57-0	Piperonal							
	oral	LD50 mg/kg	2700	Rat	Toxicology and Applied Pharmacology, 6(4	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rat	Study report (1980)	other: IFF Protocol No. DLD		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Pentane-2,3-dione, Piperonal. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics - <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 9 of 13

No data available

CAS No	Chemical name	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
	Hydrocarbons C10-C13 -	n-alkanes -	iso-alkanes -	cyclics	< 2% aromatics				
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Danio rerio	REACh Registration Dossier	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202		
120-57-0	Piperonal								
	Acute algae toxicity	ErC50	31 mg/l	72 h	Raphidocelis subcapitata	Study report (2013)	OECD Guideline 201		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons C10-C13 - n-alkanes - iso-alkanes - cyclics - < 2% aromatics	>= 3,17
	Calcium alkylnaphthalenesulfonate	> 6,6

BCF

CAS No	S No Chemical name		Species	Source
	Hydrocarbons C9-C10 - n-alkanes - isoalkanes - cyclics - <2% aromatics	144,3	calculated	Other company data (
	Hydrocarbons C10-C13 - n-alkanes - iso-alkanes - cyclics - < 2% aromatics			REACh Registration D
	Calcium alkylnaphthalenesulfonate	3,16	fish	Study report (2013)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 10 of 13

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances: hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 11 of 13

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user
Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 87,688 % (578,744 g/l)

National regulatory information

Employment restrictions: Observe employment restrictions under the Maternity Protection Directive

(92/85/EEC) for expectant or nursing mothers. Observe employment

restrictions for women of child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 12 of 13

Abbreviations and acronyms

Aerosol: Aerosols

Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure			
Aerosol 1; H222-H229	On basis of test data			
Asp. Tox. 1; H304	Calculation method			
STOT SE 3; H336	Bridging principle "Aerosols"			
Aquatic Chronic 3; H412	Calculation method			

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airway

H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains Pentane-2,3-dione, Piperonal. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.


Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Lubricating agent	PW, C	-	24	11	-	-	7, 80	

LCS: Life cycle stages
PC: Product categories

ERC: Environmental release categories TF: Technical functions

SU: Sectors of use PROC: Process categories AC: Article categories





according to Regulation (EC) No 1907/2006

4700 MultiOil Spray EV

Revision date: 07.08.2023 Product code: 70634 Page 13 of 13

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)