

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4780 Silicone Spray

UFI: M3WE-G80W-Q00G-FUSD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Company name:	Kisling Deutschland GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 5096161	
E-mail:	info@kisling.com	
Contact person:	Isabel Winter	Telephone: +49 7941 92054087
E-mail:	info@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
Skin Irrit. 2; H315
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat. No Smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 2 of 14

P271 Use only outdoors or in a well-ventilated area.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H336-H412

Precautionary statements

P102-P210-P211-P251-P271-P410+P412

2.3. Other hazards

Pressurised container: May burst if heated.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Hazardous components

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	Classification (Regulation (EC) No 1272/2008)	
109-66-0	pentane	5 - < 15 %
	203-692-4 601-006-00-1 01-2119459286-30	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066	
63148-62-9	Polydimethylsiloxane	5 - < 15 %
	Aquatic Chronic 4; H413	
	Hydrocarbons C6 - isoalkanes <5% n-hexane	1 - < 5 %
	931-254-9 01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
	Hydrocarbons C6-C7 - isoalkanes - cyclics - <5% n-hexane	1 - < 5 %
	926-605-8 01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066	
110-82-7	cyclohexane	0.1 - < 1 %
	203-806-2 601-017-00-1	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
109-66-0	203-692-4	pentane	5 - < 15 %
		inhalation: LC50 = > 25,3 mg/l (vapours); oral: LD50 = > 5000 mg/kg	
	931-254-9	Hydrocarbons C6 - isoalkanes <5% n-hexane	1 - < 5 %
		inhalation: LC50 = 73860 mg/l (vapours)	
110-82-7	203-806-2	cyclohexane	0.1 - < 1 %
		inhalation: LC50 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder. Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Water. Full water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 4 of 14

with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13 See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately. When using do not eat or drink.

Further information on handling

When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 5 of 14

Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
110-82-7	Cyclohexane	200	700		TWA (8 h)	
109-66-0	Pentane	1000	3000		TWA (8 h)	

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
109-66-0	pentane			
	Worker DNEL, long-term	inhalation	systemic	3000 mg/m ³
	Worker DNEL, long-term	dermal	systemic	432 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	643 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	214 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	214 mg/kg bw/day
	Hydrocarbons C6 - isoalkanes <5% n-hexane			
	Worker DNEL, long-term	inhalation	systemic	5306 mg/m ³
	Worker DNEL, long-term	dermal	systemic	13964 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	1131 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	1377 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	1301 mg/kg bw/day
110-82-7	cyclohexane			
	Worker DNEL, long-term	inhalation	systemic	700 mg/m ³
	Worker DNEL, acute	inhalation	systemic	1400 mg/m ³
	Worker DNEL, long-term	inhalation	local	700 mg/m ³
	Worker DNEL, acute	inhalation	local	1400 mg/m ³
	Worker DNEL, long-term	dermal	systemic	2016 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	206 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	412 mg/m ³
	Consumer DNEL, long-term	inhalation	local	206 mg/m ³
	Consumer DNEL, acute	inhalation	local	412 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	1186 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	59,4 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 6 of 14

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
109-66-0	pentane	
Freshwater		0,23 mg/l
Freshwater (intermittent releases)		0,88 mg/l
Marine water		0,23 mg/l
Freshwater sediment		1,2 mg/kg
Marine sediment		1,2 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,6 mg/l
Soil		0,55 mg/kg
110-82-7	cyclohexane	
Freshwater		0,0447 mg/l
Freshwater (intermittent releases)		0,009 mg/l
Marine water		0,00447 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		0,36 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,24 mg/l
Soil		0,694 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Suitable eye protection: goggles
EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Suitable material:

Thickness of the glove material > 0,45mm
> 240 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Work in well-ventilated zones or use proper

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 7 of 14

respiratory protection. Filtering device with filter or ventilator filtering device of type: A (EN 14387)

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	colourless	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Flammability:		not applicable
Lower explosion limits:		1,0 vol. %
Upper explosion limits:		15,0 vol. %
Flash point:		not applicable
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not applicable
Water solubility:	The substance is not soluble in water.	
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		4000 hPa
(at 20 °C)		
Vapour pressure:		7000 hPa
(at 50 °C)		
Density (at 20 °C):		0,61 g/cm ³
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Heating may cause an explosion. Vapours can form explosive mixtures with air.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated. Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent, strong

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 8 of 14

ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
109-66-0	pentane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 423
	inhalation (4 h) vapour	LC50 > 25,3 mg/l	Rat	Secondary source (1993)	OECD Guideline 403
	Hydrocarbons C6 - isoalkanes <5% n-hexane				
	inhalation (4 h) vapour	LC50 73860 mg/l	Rat	Industrial Medicine, Vol. 39, No. 5, May	OECD Guideline 403
110-82-7	cyclohexane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 5540 mg/l	Rat	Study report (1981)	OECD Guideline 403

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 9 of 14

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name		Dose	[h] [d]	Species	Source	Method
	Aquatic toxicity						
	Hydrocarbons C6 - isoalkanes <5% n-hexane						
	Acute fish toxicity	LL50 mg/l	18,27	96 h	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute algae toxicity	ErC50 mg/l	13,56	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EL50 mg/l	31,9	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC mg/l	4,089	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	7,138	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
110-82-7	cyclohexane						
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Raphidocelis subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987)	OECD Guideline 202

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
109-66-0	pentane	3,45
	Hydrocarbons C6 - isoalkanes <5% n-hexane	3,6
110-82-7	cyclohexane	3,44

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 10 of 14

BCF

CAS No	Chemical name	BCF	Species	Source
109-66-0	pentane	171	Pimephales promelas	QSAR in Environmenta
	Hydrocarbons C6 - isoalkanes <5% n-hexane	501,187	Pimephales promelas	QSAR in Environmenta
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.

12.4. Mobility in soil

Product is easily volatile.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 11 of 14



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 12 of 14

IATA-max. quantity - Cargo:

150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 57

2010/75/EU (VOC):

93,7 %

Information according to 2012/18/EU
(SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information

Regulation (EC) No. 648/2004 [Detergents regulation].

Aerosol Directive (75/324/).

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 13 of 14

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).
 Aerosol: Aerosols
 Flam. Liq: Flammable liquid
 Asp. Tox: Aspiration hazard
 Skin Irrit: Skin irritation
 STOT SE: Specific target organ toxicity - single exposure
 Aquatic Acute: Acute aquatic hazard
 Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H229 Pressurised container: May burst if heated.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4780 Silicone Spray

Revision date: 05.01.2023

Product code: 94568

Page 14 of 14

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Surface modifier	-	-	14	-	-	-	-	3
2	Washing and cleaning products	IS, PW, C	-	35	7, 11, 19, 28	4, 8d	-	105	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)