



2250

Epoxy-paint primer

Product description

1K anticorrosive primer, ideal for repairs and painting parts. Active rust protection pigments provide long-lasting protection against corrosion. The fast drying formulation allows time-saving work.

Advantages

- Very good adhesion and high filling
- Overpaintable within 10-15 minutes
- Sealant compatible and easy to sand
- Very economical and productive in use

Application fields

Metalworking, garages

Application

1. Base needs to be clean, dry and free of grease. Remove any loose rust, paint and dirt using steel wire brushes, scrapers etc. Sand down problematic bases.
2. Shake the can well before use.
3. Spray in 2-3 spray coats at a distance of 20-30 cm.



Technical Data

Property	Value
Chemical base	Epoxy-based paint
Colour	White grey, red brown
Dry layer thickness	ca. 30 µm
Drying conditions at 23°C	<ul style="list-style-type: none"> • Dust dry 10-15 min • Touch dry 25-30 min • Fully dry 24 h • overpaintable 15 -20 min • sandable 20 min
Forced drying	50 °C / 10 min 100 °C / 5 min
Storage stability	24 months
Storage temperature	+5°C to +35°C

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

Available containers

Container	Volume	Colour
Spray can	400 ml	White grey
Spray can	400 ml	Red brown

Liability notices

This technical information leaflet is the result of careful testing and used to advise our customers.

The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.

KERONA GmbH
 Zeilbaumweg 15
 D-74613 Öhringen
 Phone: +49 7941-9205 4080
 mail@kerona.de
 www.kerona.de