

# TECHNICAL DATA SHEET

## 2260 Paint primer 750 ml

<b>Description</b>	Anti-corrosion primer based upon alkyd resin for metal surfaces. Excellent adhesion to different substrates. Economical and universal primer also for aluminum, galvanized surfaces and various plastics. Overcoatable with all conventional paint systems.
<b>Advantages</b>	Salt spray resistant according to DIN EN ISO 9227 - excellent adhesion on metals, paint and plastics - fast drying - high filling capacity
<b>Application fields</b>	Auto repair shops, metalworking
<b>Application</b>	1. The substrate must be dry, free of grease, dust and rust. Sand problem substrates and old paintwork. 2. Stir well before use. 3. Apply with a brush or spray on with a spray gun. Set to 30 s for HVLP spraying with nitro thinner, no thinning is necessary for airless spraying.

### Technical data

<b>Chemical base</b>	Synthetic resin
<b>Colour</b>	Light grey, red brown
<b>Density</b>	1,28 g/ml
<b>Curing</b>	24 h at room temperature, overpaintable after 120 min.
<b>Viscosity (DIN 4 mm)</b>	60 - 65 s
<b>Consumption</b>	ca. 120 g/m <sup>2</sup> at 40 µm recommended layer thickness (VdL-RL 08)
<b>Propellant</b>	-
<b>Application temperature</b>	15°C - 25°C
<b>Storage temperature</b>	5°C - 35°C
<b>Shelf life</b>	12 months
<b>Packaging</b>	750 ml tin can
<b>Product variants</b>	A226075001 red brown 750 ml A226075002 white grey 750 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.