

TECHNICAL DATA SHEET

2295 Rust converter professional 400 ml

Description	Neutralizes the rust layer and stops rust development. The anticorrosion paint with rust converting properties is ideally suited for painting over rust-prone older vehicles. Very easy and fast to apply. Without stoichiometry effect – contains no acid which leads to metal corrosion when overdosed.
Advantages	Quick and easy application - epoxy binder for excellent overcoatability - reliable protection against corrosion - neutral formulation
Application fields	Auto repair shops, metalworking
Application	1. The surface must be dry, grease- and dust-free. Grind problematic substrates and old paintwork. 2. Shake can well before use. 3. Apply sparingly; spray in 2-3 spray coats at a distance of 25-30 cm.

Technical data

Chemical base	Epoxy resin
Colour	Transparent
Density	0,73 g/ml
Curing	24 h at room temperature, overpaintable after 120 min.
Recommended layer thickness	ca. 10 µm
Temperature resistance	< 180°C
Propellant	Dimethylether
Application temperature	15°C - 25°C
Storage temperature	5°C - 25°C
Shelf life	24 months
Packaging	400 ml aerosol
Product variants	A229540001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.

