



2295 Rust converter professional

Product description

Neutralizes the rust layer and stops rust development. The anticorrosion paint with rust converting properties is ideally suited for painting over rust-prone older vehicles. Very easy and fast to apply. Without stoichiometry effect – contains no acid which leads to metal corrosion when overdosed.

Advantages

- Quick and easy application
- Epoxy binder for excellent overcoatability
- Reliable protection against corrosion
- Neutral formulation

Application fields

Automobile workshops, home and garden

Application

1. The surface must be dry, grease- and dust-free. Grind problematic substrates and old paintwork.
2. Shake can well before use.
3. Apply sparingly; spray in 2-3 spray at a distance of 25-30 cm.
4. Apply topcoat when dry (about 2 hours).



Technical Data

Property	Value
Chemical basis	Epoxy-paint with rust-converting additives
Colour	Transparent (after rust conversion: black)
Temperature stability	< 180°C
Overcoatable after	2 hours
Storage stability	24 months
Recommended storage	5°C - 25°C

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

Available containers

Container	Volume
Spray can	400 ml

Liability notices

This technical information leaflet is the result of careful testing and used to advise our customers.

The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery.

We reserve the right to make any changes in this product information due to new knowledge.

KERONA GmbH
Zeilbaumweg 15
D-74613 Öhringen
Phone: +49 7941-9205 4080
mail@kerona.de
www.kerona.de