

# TECHNICAL DATA SHEET

## 2810 Adhesive Spray 400 ml

<b>Description</b>	The spray adhesive is suitable for permanent bonding of objects. The formulation based on a particularly high-quality, solvent-based synthetic rubber adhesive can be used for contact or assembly bonding. The quick-drying, solvent-based adhesive from the aerosol can is quick and easy to use and has been specially developed for light materials such as carpets, fabrics, paper, cork, plastics and many other materials.
<b>Advantages</b>	Quick and easy to use - high adhesive power - suitable for polystyrene, foam rubber, felt, paper, cardboard, wood, metal and many plastics
<b>Application fields</b>	Auto repair shops, industry, metalworking, Household, DIY
<b>Application</b>	1. Shake vigorously before application. The roughened surfaces to be glued must be free of grease and dust. Check the suitability of the spray adhesive on various surfaces by means of preliminary tests. 2. The quantity applied should be increased for absorbent substrates (wood, felt, etc.). Spray distance about 20-25 cm. The adhesive must be applied to both parts separately. Spray upside down after use to avoid clogging of the spray nozzle. 3. Depending on the temperature and layer thickness, the adhesive should dry for 5 to 15 minutes. 4. Then the parts are put together and pressed. A later correction is only possible with a short flash-off time before assembling. Do not strain the bond point within 24 hours.

### Technical data

<b>Chemical base</b>	Butyl caoutchouc (butyl rubber)
<b>Colour</b>	Transparent
<b>Density</b>	0,68 g/ml
<b>Temperature resistance</b>	-25°C - +45°C
-	-
-	-
<b>Propellant</b>	Propane/butane
<b>Application temperature</b>	5°C - 35°C
<b>Storage temperature</b>	5°C - 25°C
<b>Shelf life</b>	12 months
<b>Packaging</b>	400 ml aerosol
<b>Product variants</b>	A281040001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.