
TECHNICAL DATA SHEET

2810 Adhesive Spray 400 ml

Product description	The spray adhesive is suitable for the permanent bonding of objects. The formulation, based on a particularly high-quality, solvent-based synthetic rubber adhesive, can be used for contact- or assembly bonding.
Advantages	Quick and easy to use - High adhesive power - Suitable for polystyrene, foam rubber, felt, paper, cardboard, wood, metal and many plastics
Application fields	auto repair shops, industry, metalworking, Household, DIY
Application	1. Shake vigorously before application. The roughened surfaces to be glued must be free of grease and dust. Check the suitability of the spray adhesive on various surfaces by means of preliminary tests. 2. The quantity applied should be increased for absorbent substrates (wood, felt, etc.). Spray distance about 20-25 cm. The adhesive must be applied to both parts separately. Spray upside down after use to avoid clogging of the spray nozzle. 3. Depending on the temperature and layer thickness, the adhesive should dry for 5 to 15 minutes. 4. Then the parts are put together and pressed. A later correction is only possible with a short flash-off time before assembling. Do not strain the bond point within 24 hours.

Technical Data

1	2
Ingredient	Butyl caoutchouc (butyl rubber)
Colour	transparent
Application temperature	5°C - 35°C
Shelf life	12 month(s)
Storage temperature	5°C - 25°C
Verpackung	Aerosols
Temperature resistance	-25°C - +45°C

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.