

TECHNICAL DATA SHEET

3300 Impregnation Spray

Description	Textile and leather impregnation for use on synthetic and semi-synthetic textiles. Ideal water and oil repellent properties for convertible tops, awnings or work / leisure wear. Especially abrasion resistant.
Advantages	Excellent oil, water and dirt repellency - suitable for workwear and outdoor clothing - environmentally friendly formulation - PFOA, PFOS, APEO-free
Application fields	Convertible roofs, home textiles, work / leisure wear
Application	1. Read instructions before use. 2. The fabric must be clean, dry and free of grease. 3. Spray at a distance of about 15-20 cm. 4. Allow to dry completely after treatment. Note: Remove excess material from adjacent, non-textile surfaces.

Technical data

Chemical base	Solvent-based fluoropolymer solution
Colour	Transparent
Density	0,68 g/ml
Curing	1 h at room temperature
Substrate	Textiles, leather, paper
Repellency	Isopropanol Test (PES): 7 (INDA IST 80.8) Spray Test (PES): 100 (AATCC 22-1996) Oleo Test (PES): 4 (AATCC 118-1997)
Propellant	Propane/butane
Application temperature	10°C - 25°C
Storage temperature	5°C - 25°C
Shelf life	24 months
Packaging	250 ml / 400 ml aerosol 500 ml trigger bottle
Product variants	A330025001 250 ml A330040001 400 ml A330050001 500 ml Trigger

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.

