

## TECHNICAL DATA SHEET

### 3300 Impregnation Spray

<b>Product description</b>	Textile and leather impregnation for use on synthetic and semi-synthetic textiles. Ideal water and oil repellent properties for convertible tops, awnings or work / leisure wear.
<b>Advantages</b>	Excellent oil, water and dirt repellency - Suitable for workwear and outdoor clothing - Environmentally friendly formulation - PFOA, PFOS, APEO-free
<b>Technology</b>	KENA BIONICS
<b>Application fields</b>	Convertible roofs, home textiles, work / leisure wear
<b>Application</b>	1. Read instructions before use. 2. The fabric must be clean, dry and free of grease. 3. Spray at a distance of about 15-20 cm. 4. Allow to dry completely after treatment. Note: Remove excess material from adjacent, non-textile surfaces.

#### Technical Data

1	2
Ingredient	Fluoropolymers
Colour	transparent
Curing	60 min.
Surfaces	Textiles
Durability	IPA Test (PES): 7 (INDA IST 80.8)
Durability	Spray Test (PES): 100 (AATCC 22-1996)
Durability	Oleo Test (PES): 4 (AATCC 118-1997)
Storage temperature packaging	5°C - 25°C
Application temperature	Aerosols
Storage temperature	10°C - 25°C
Shelf life	5°C - 25°C
	24 month(s)

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.