

## 4615

### Adhesive lubricant spray

#### Product description

The product is a highly viscous lubricant, particularly effective against wear, oxidation and corrosion. After spraying, the active ingredient creeps into deep crevices. A well-adhering lubricating film remains on the surface after the solvent has evaporated.

#### Advantages

- Protects against corrosion and wear
- No staining
- Temperature resistant (-30°C to +200°C)

#### Application fields

Automobile, metal working

#### Application

1. Shake well before use.
2. Spray from approx. 25 cm.



#### Technical Data

Property	Value
Physical state	Aerosol
Chem. Base	Mineral oil with additives
Colour	Yellowish
Application temperature	+5°C to max +25°C
Density	0,77 g/ml (20°C)
Storage stability	24 months
Recommended storage	-5°C to max +30°C

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

#### Available Containers

Container	Volume
Spray can	400 ml

#### Liability notices

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.

KERONA GmbH  
Zeilbaumweg 15  
D-74613 Öhringen  
Fon: +49 7941-9205 4080  
mail@kerona.de  
www.kerona.de