

TECHNICAL DATA SHEET

4625 PTFE Spray 400 ml

Description	Lubricant, slip agent and release agent for metal, rubber, plastics and other materials based on silicone oil and PTFE components. It is particularly suitable for applications in which mineral oils or MoS ₂ cannot be used due to the risk of dirt. It is often used for gear parts, bushings, hinges, lock cylinders, sunroof mechanisms, snap locks, pedal rods or V-belts. It fills microscopic fissures and protects against moisture and corrosion. The dry lubricant adheres very well to most surfaces.
Advantages	Fat-free - water-repellent - non-stick - temperature resistant from - 190°C to + 260°C
Application fields	Auto repair shops, industry, metalworking
Application	1. Shake the container well before use. 2. Spray the lubrication point. 3. Repeat if necessary

Technical data

Chemical base	PTFE / silicone oils
Colour	Milky white
Density	0,60 g/ml
Temperature resistance	-190°C - 260°C
Solvent (%)	92,5
-	-
Propellant	Propane/butane
Application temperature	5°C - 35°C
Storage temperature	5°C - 25°C
Shelf life	24 months
Packaging	400 ml aerosol
Product variants	A462540001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.