

# TECHNICAL DATA SHEET

## 4645 Copper paste spray 400 ml

<b>Description</b>	Copper paste spray is used for assembly lubrication of screw connections that are exposed to high temperatures and corrosive influences during operation. Application examples are screw connections on superheated steam lines, exhaust pipe and combustion chamber screw connections, fastening screws for gas and oil burners. The use of copper paste spray prevents seizing at high temperatures and long operating times.
<b>Advantages</b>	High temperature application range: -30 ° C to + 1100 ° C - allows for non-destructive dismantling - suitable for corrosive environments and exposure to moisture
<b>Application fields</b>	Auto repair shops, industry, metalworking
<b>Application</b>	Remove residues (oxide, paint and scale layers, old lubricants) from surfaces. Ideally mechanically using a wire brush and a solvent cleaner. 1. Shake the container well before use. 2. Spray onto respective area. 3. Repeat if necessary.

### Technical data

<b>Chemical base</b>	Copper
<b>Colour</b>	Copper
<b>Density</b>	0,65 g/ml
<b>Temperature resistance</b>	-30°C - +1100°C
<b>Solvent (%)</b>	71,4
-	-
<b>Propellant</b>	Propane/butane
<b>Application temperature</b>	5°C - 35°C
<b>Storage temperature</b>	5°C - 25°C
<b>Shelf life</b>	24 months
<b>Packaging</b>	400 ml aerosol
<b>Product variants</b>	A464540001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.