
TECHNICAL DATA SHEET

4650 Drilling and cutting oil Spray 400 ml

Product description	Special high-performance lubricating oil without aggressive additives in metal processing, e.g. for thread cutting, reaming, sawing, drilling, turning, scraping, punching and milling. The product can be used with all types of steel, cast iron, stainless steel, copper, brass, aluminum and their alloys. Leads to significantly longer service lives for drilling and cutting tools and reduced production scrap. Surface damage is avoided.
Advantages	High heat resistance - biodegradable - very economical
Application fields	auto repair shops, industry, metalworking
Application	1. Shake the container well before use. 2. Spray onto respective area. 3. Repeat if necessary. Copper and copper alloys must be washed off after processing.

Technical Data

1	2
Ingredient	Hydrocarbons
Colour	red
Application temperature	5°C - 35°C
Shelf life	24 month(s)
Storage temperature	5°C - 25°C
Verpackung	Aerosols

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.