
TECHNICAL DATA SHEET

4740 Rust dissolver MoS2 Spray 400 ml

Product description	Rust remover with MoS ₂ -based high-pressure lubrication to loosen tight connections and Fittings. Due to the excellent creep effect, the rust remover penetrates into deep-seated spaces. Also protects against corrosion. Due to the molybdenum disulfide (MoS ₂), the product can be used above all at high temperatures and under extreme pressure loads. Molybdenum disulfide has the lowest coefficient of friction of various known lubricants.
Advantages	Lubrication even under high pressure loads - eliminates squeaking and creaking - very temperature-resistant - loosens stuck parts
Application fields	auto repair shops, industry, metalworking
Application	1. Shake the container well before use. 2. Spray onto respective area. 3. Repeat if necessary.

Technical Data

1	2
Ingredient	Hydrocarbons / MoS ₂
Colour	grey
Application temperature	5°C - 35°C
Shelf life	24 month(s)
Storage temperature	5°C - 25°C
Verpackung	Aerosols

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.