

4740 Rust dissolver MoS2 Spray 400 ml

Description	Rust dissolver with MoS2-based high-pressure lubrication for loosening stuck connections and screw connections. Due to the excellent creeping effect, the rust dissolver penetrates deep-seated spaces. Provides additional protection against corrosion and displaces water and moisture. Due to the molybdenum disulphide (MoS2), the product can be used primarily at high temperatures and under extreme pressure loads. Molybdenum disulfide has the lowest coefficient of friction of any known lubricant.
Advantages	Lubrication even under high pressure loads - eliminates squeaking and creaking - very temperature-resistant - loosens stuck parts
Application fields	Auto repair shops, industry, metalworking
Application	1. Shake the container well before use. 2. Spray onto respective area. 3. Repeat if necessary. Note: Check material compatibility before use.

Technical data

Chemical base	Mineral oil / MoS2
Colour	Grey
Density	0,68 g/ml (20°C)
VOC (%)	100
-	-
-	-
Propellant	Propane/butane
Application temperature	5°C - 35°C
Storage temperature	5°C - 25°C
Shelf life	24 months
Packaging	400 ml aerosol
Product variants	A474040001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.