

4780 Silicone Spray

Description Silicone spray is a grease-free protective, lubricant, release and maintenance agent for

plastics, wood, rubber and metals. The product is also suitable for electrical insulation and impregnation. Incidentally, it also serves to protect against corrosion. The product is largely odorless and behaves neutrally. Rubber parts are cared for, they do not become brittle and do not stick together. Plastic parts have a slight shine. Moving parts stop squeaking. Excellent release agent for molding and injection molding and suitable as an assembly aid

for hose connections.

Advantages Transparent lubrication - good electrical resistance - water-repellent and antistatic

Application fields Auto repair shops, industry, metalworking, electronics

Application 1. Shake the can before use. 2. Spray sparingly onto the surface to be treated 3. Wipe with a

clean, dry cloth.

Technical data

Chemical base	Silicone oil
Colour	Transparent
Density	0,61 g/ml (20°C)
VOC (%)	93,7
Temperature resistance	-60 °C - +200 °C
-	-
Propellant	Propane/butane
Application temperature	5°C - 35°C
Storage temperature	5°C - 25°C
Shelf life	24 months
Packaging	400 ml aerosol
	500 ml aerosol
Product variants	A478040001 400 ml
	A478050001 500 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.